Kartell SpA DIVISIONE LABWARE	TECHNICAL DATA SHEET ITEM 2630	Mod. AQ 001 Rev. 0 del 25/09/2003

TECHNICAL SPECIFICATIONS

Trade name	Cuvettes for Fibrintimer
Use	Determination of coagulation time
Material	Polystyrene PS
Other	Supplied with 500 metallic mixer

DIMENSIONAL SPECIFICATIONS

Height	mm. 34,50
Diameter	mm. 11,90
General dimensional tolerance	mm. +/- 0,05

GENERAL FEATURES

CE mark	Yes
Autoclavability	No
Sterilization	To be effected by radiations
Food contact suitable	Yes

CHEMICAL RESISTANCE

Categories of substances	Reference	Concen. %	T. 20°	T. 40°	T.° 60
Inorganic acid	Sulphuric acid	98	C	-	-
Organic acid	Benzoic acid	100	B	B	B
Alcohol	Ethanol	100	B	C	-
Aldehydes	Acetaldehyde	100	C	-	-
Inorganic alkali	Sodium hydroxide	50	A	A	A
Organic alkali	Aniline	100	C	-	-
Ketone	Acetone	100	-	-	-
Esther	Ethyl acetate	100	C	-	-
Hydrocarbons, halogenated	Dichloroethylene	100	C	-	-
Hydrocarbons, aromatic	Benzene	100	C	-	-
Hydrocarbons, linear	Hexane	100	C	-	-
Supersolvent	Tetrahydrofuran	100	C	-	-

Legenda (not applicable if neglected):

- **A: fair resistence;** exposure (30 days) to the chemical does not cause any damage.
- **B: sufficient resistence;** exposure causes damage of poor importance, which sometimes is only temponary.
- **C: poor resistence;** exposure to chemical is not allowed, or cases immediate permanent damage.

Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing..

PACKAGING

Bag	Pcs. 500
Box	Pcs. 10000

DOMINIQUE DUTSCHER SAS

Quality Assurance

Massimiliano Capitanio

Technical Direction

Guido Borona

This paper is an electronic print-out: signature is not requested