Biosigma SpA
a Dominique Dutscher Company
Via Valletta, 6 | 30010 Cantarana di Cona (VE), Italy | Tel. ++39 0426 302224 (r.a.) |
E-mail info@biosigmaeu.com | http://www.biosigma.com | www.biosigma.it

SCHEDA TECNICA PRODOTTO – TECHNICAL DATA SHEET

MICROTUBI AMBRATI / *AMBER MICROTUBES*
ClearLine®



PER USO GENERICO / *FOR GENERIC USE*

Per soddisfare anche le più elevate esigenze nelle numerose applicazioni biotecnologiche, Biosigma SpA offre una vasta gamma di dispositivi monouso con elevati livelli di purezza. La purezza dei prodotti *ClearLine®* si ottiene soprattutto evitando qualsiasi contaminazione già durante la produzione.
Ogni lotto di produzione viene controllato e certificato.

To satisfy the highest demands in many biotechnological applications, Biosigma Srl offers a wide range of disposable devices with high levels of purity. The purity of the products ClearLine ® is achieved especially by avoiding any contamination during production. ***Each production batch is inspected and certified.***

Biosigma SpA

CERTIFICA
che i MICROTUBI AMBRATI della linea ClearLine® sono completamente privi di :

- **DNA umano**
- **PCR inibitori**
- **DNasi**
- **RNasi**
- **Pirogeni**
- **ATP**

CERTIFIES
that AMBER MICROTUBES ClearLine® are completely free of:

- ***human DNA***
- ***PCR inhibition***
- ***DNase***
- ***RNase***
- ***Pyrogens***
- ***ATP***

Codice *Code*	Descrizione *Descriptions*	*Colore* *Color*	Volume ml	Dimensioni mm *Dimensions mm*	Imballo pz *Packaging pcs*
CL026/AM	Conetto con tappo tipo Eppendorf in PP. *Microtube with cap Eppendorf type in PP.*	Ambrato *Amber*	0,5	Ø 7,8 H 30	4 x 500
CL022/AM	Conetto con tappo tipo Eppendorf in PP. *Microtube with cap Eppendorf type in PP.*	Ambrato *Amber*	1,5	Ø 10,8 H 41	2 x 500
CL0269/AM	Conetto con tappo tipo Eppendorf in PP. *Microtube with cap Eppendorf type in PP.*	Ambrato *Amber*	2	Ø 10,8 H 42	2 x 500

DOMINIQUE DUTSCHER SAS

SCHEDA TECNICA PRODOTTO – TECHNICAL DATA SHEET

CARATTERISTICHE PRINCIPALI:

- Semitrasparenti, permettono la visione del campione
- Proteggono i campioni dalla luce
- In Polipropilene (PP)
- Centrifugabili a 16.400 rpm - 25.000 x g,
- Congelabili fino a -80 °C;
- Autoclavabili aperti a 121°C per 20 minuti,
- Graduati con superficie scrivibile, 1,5 - 2 ml
- Tappo con superficie scrivibile e perforabile,
- Non sterili

MAIN CHARACTERISTICS:

- *Semi-transparent, it allows the sample visual-check*
- *Protecting samples from light*
- *In Polypropylene (PP)*
- *Centrifuged at*: 16.400 rpm - 25.000 x g,
- *Freezing up to -80 °C,*
- *Autoclavable open at +121°C for 20 minutes,*
- *Graduated with writing area, 1,5 - 2 ml*
- *Cap with writing area and pierceable,*
- *Not sterile*

DEFINIZIONE DEL FABBRICANTE/ ***MANUFACTURER DEFINITION*****:**

BIOSIGMA SpA
Via Valletta, 6 30010 - Cantarana di Cona (VE) - ITALY
Tel. +39.0426.302224 - Fax +39.0426.302228
E-mail: info@biosigma.com http://www. biosigma.com

DOMINIQUE DUTSCHER SAS