

UV Master ® technology
 Stainless steel frame
 Adjustable UV safety screen
 Ondulex ® reflector for higher UV output
 Unlimited filter life expectancy for 312 and 365nm
 Adjustable dual intensity selector (100%-70%)
 100/115/230 volt, 50/60 Hz



● Description

UV standard

The ECX transilluminator is both compact and economical for laboratories with budget in mind. The fully adjustable UV safety screen can be positioned to suit the operator's viewing angle against exposure to harmful UV rays. The High/Low intensity selection is ideal to switch from short gel visualization to longer preparative work.

● Ordering codes

Code	Description	nm	Filter (mm)	Tubes	Intensity ($\mu\text{W}/\text{cm}^2$)
VLECX-15M	High / Low intensity	312	150 x 150	4 x 8-watt	10000
VLECX-15C	High / Low intensity	254	150 x 150	4 x 8-watt	7000
VLECX-20M	High / Low intensity	312	200 x 200	6 x 8-watt	10000
VLECX-20C	High / Low intensity	254	200 x 200	6 x 8-watt	7000
VLECX-20L	High / Low intensity	365	200 x 200	6 x 8-watt	7000
VLECX-26M	High / Low intensity	312	210 x 260	6 x 8-watt	10000
VLECX-26C	High / Low intensity	254	210 x 260	6 x 8-watt	7000

DOMINIQUE DUTCHER