

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Ethyl acetate  
SDS-number : 000000020226  
Type of product : Substance  
Remarks : SDS according to Art. 31 of Regulation (EC) 1907/2006.  
  
Chemical name : ethyl acetate  
Index-No. : 607-022-00-5  
REACH Registration Number : no data available

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Laboratory chemicals  
Uses advised against : none

#### 1.3. Details of the supplier of the safety data sheet

Company : Honeywell International Inc.      Honeywell International, Inc.  
115 Tabor Road      115 Tabor Road  
07950-2546 Morris Plains      Morris Plains, NJ 07950-2546  
USA      USA  
  
Telephone :  
For further information, please contact: : [SafetyDataSheet@Honeywell.com](mailto:SafetyDataSheet@Honeywell.com)

#### 1.4. Emergency telephone number

Emergency telephone number : +1-703-527-3887 (ChemTrec-Transport)  
+1-303-389-1414 (Medical)  
Country based Poison Control Center : see chapter 15.1

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

### SECTION 2: Hazards identification


#### 2.1. Classification of the substance or mixture

##### REGULATION (EC) No 1272/2008

Flammable liquids Category 2  
H225 Highly flammable liquid and vapour.  
Eye irritation Category 2  
H319 Causes serious eye irritation.  
Specific target organ toxicity - single exposure Category 3 - Central nervous system  
H336 May cause drowsiness or dizziness.

#### 2.2. Label elements

##### REGULATION (EC) No 1272/2008

|                          |   |   |
|--------------------------|---|---|
| Hazard pictograms        | : |    |
| Signal word              | : | Danger  |
| Hazard statements        | : | H225 Highly flammable liquid and vapour.<br>H319 Causes serious eye irritation.<br>H336 May cause drowsiness or dizziness.<br>EUH066 Repeated exposure may cause skin dryness or cracking.  |
| Precautionary statements | : | P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P243 Take precautionary measures against static discharge.<br>P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.<br>P280 Wear protective gloves/ eye protection/ face protection.<br>P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.<br>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. |

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

P308 + P313

Continue rinsing.  
IF exposed or concerned: Get medical  
advice/ attention.

### 2.3. Other hazards

Aspiration hazard if swallowed - can enter lungs and cause damage. May form explosive mixtures in air.  
Results of PBT and vPvB assessment, see chapter 12.5.

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

| Chemical name | CAS-No.<br>Index-No.<br>REACH Registration<br>Number<br>EC-No. | Classification 1272/2008   | Concentration | Remarks |
|---------------|--|--|---------------|---------|
| ethyl acetate | 141-78-6<br>607-022-00-5<br>205-500-4                          | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336;<br>Central nervous system<br>EUH066 | 100 %         |         |

### 3.2. Mixture

Not applicable

Occupational Exposure Limit(s), if available, are listed in Section 8.  
For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

*General advice:*

First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

*Inhalation:*

In case of accident by inhalation: remove casualty to fresh air and keep at rest. If symptoms persist, call a physician.

*Skin contact:*

After contact with skin, wash immediately with plenty of soap and water. Call a physician if irritation develops or persists.

*Eye contact:*

Rinse immediately with plenty of water, also under the eyelids. Protect unharmed eye. Call a physician immediately.

*Ingestion:*

When swallowed, allow water to be drunk. Do NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

See Section 11 for more detailed information on health effects and symptoms.

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

*Suitable extinguishing media:*

Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder

*Extinguishing media which shall not be used for safety reasons:*

High volume water jet

#### 5.2. Special hazards arising from the substance or mixture

Flash back possible over considerable distance.  
Cool closed containers exposed to fire with water spray.  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Do not breathe vapours or spray mist.  
Remove all sources of ignition.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so.

#### 6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

Pick for disposal in tightly closed containers  
Use low-sparking handtools and explosion-proof electrical equipment

### 6.4. Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

*Advice on safe handling:*

Exhaust ventilation at the object is necessary. Use explosion-proof equipment.

*Advice on protection against fire and explosion:*

The product is easily combustible. Vapours may form explosive mixtures with air. Flash back possible over considerable distance. Labeling danger zone "risk of explosion". Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep product and empty container away from heat and sources of ignition.

*Hygiene measures:*

Recommended preventive skin protection Keep working clothes separately. General industrial hygiene practice.

*Temperature class:*

T2

### 7.2. Conditions for safe storage, including any incompatibilities

*Further information on storage conditions:*

Keep only in the original container in a cool, well-ventilated place. Keep container dry. Do not leave vessels/containers open Keep away from heat. Keep away from direct sunlight.

*Advice on common storage:*

Do not store together with: Oxidizing agents Acids Bases

### 7.3. Specific end use(s)

no additional data available

**Ethyl acetate**

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits:**

| Components    | Basis / Value type | Value / Form of exposure           | Exceeding Factor | Remarks    |
|---------------|--------------------|------------------------------------|------------------|------------|
| ethyl acetate | EH40 WEL<br>STEL   | 400 ppm                            |                  |            |
| ethyl acetate | EH40 WEL<br>TWA    | 200 ppm                            |                  |            |
| ethyl acetate | EU ELV<br>STEL     | 1.468 mg/m <sup>3</sup><br>400 ppm |                  | Indicative |
| ethyl acetate | EU ELV<br>TWA      | 734 mg/m <sup>3</sup><br>200 ppm   |                  | Indicative |
| ethyl acetate | EH40 WEL<br>STEL   | 1.468 mg/m <sup>3</sup><br>400 ppm |                  |            |
| ethyl acetate | EH40 WEL<br>TWA    | 734 mg/m <sup>3</sup><br>200 ppm   |                  |            |

STEL - Short term exposure limit  
TWA - Time weighted average

**DNEL/ PNEC-Values**

| Component     | End-use/impact                          | Exposure duration | Value                  | Exposure routes | Remarks |
|---------------|---|-------------------|------------------------|-----------------|---------|
| ethyl acetate | Workers /<br>Acute systemic effects     |                   | 1468 mg/m <sup>3</sup> | Inhalation      |         |
| ethyl acetate | Workers /<br>Acute local effects        |                   | 1468 mg/m <sup>3</sup> | Inhalation      |         |
| ethyl acetate | Workers /<br>Long-term systemic effects |                   | 734 mg/m <sup>3</sup>  | Inhalation      |         |
| ethyl acetate | Workers /<br>Long-term                  |                   | 63mg/kg bw/d           | Skin contact    |         |

**Ethyl acetate**

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

|               |  |  |              |              |  |
|---------------|--|--|--------------|--------------|--|
|               | systemic effects                       |  |              |              |  |
| ethyl acetate | Workers / Long-term local effects      |  | 734 mg/m3    | Inhalation   |  |
| ethyl acetate | Consumers / Acute systemic effects     |  | 734 mg/m3    | Inhalation   |  |
| ethyl acetate | Consumers / Acute local effects        |  | 734 mg/m3    | Inhalation   |  |
| ethyl acetate | Consumers / Long-term systemic effects |  | 367 mg/m3    | Inhalation   |  |
| ethyl acetate | Consumers / Long-term local effects    |  | 367 mg/m3    | Inhalation   |  |
| ethyl acetate | Consumers / Long-term systemic effects |  | 37mg/kg bw/d | Skin contact |  |

| Component     | Environmental compartment / Value | Remarks |
|---------------|-----------------------------------|---------|
| ethyl acetate | Fresh water: 0,26 mg/l            |         |
| ethyl acetate | Soil: 0,22 mg/kg                  |         |
| ethyl acetate | Sewage treatment plant: 650 mg/l  |         |
| ethyl acetate | Sediment: 0,34 mg/kg              |         |



## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

### 8.2. Exposure controls

#### Occupational exposure controls

The Personal Protective Equipment must be in accordance with EN standards:respirator EN 136, 140, 149; safety glasses EN 166; protective suit: EN 340, 463, 468, 943-1, 943-2; gloves EN 374, 511; safety shoes EN-ISO 20345.

Take off all contaminated clothing immediately.

#### Personal protective equipment

##### *Respiratory protection:*

In the case of vapour formation use a respirator with an approved filter.

##### *Hand protection:*

Glove material: butyl-rubber

Break through time: > 120 min

Glove thickness: 0,7 mm

Butoject® 898

Gloves must be inspected prior to use.

Replace when worn.

Remarks:Supplementary note: The specifications are based on information and tests from similar substances by analogy.

Due to varying conditions ( e.g.temperature or other strains) it must be considered that the usage of a chemical protective glove in practice may be much shorter than the permeation time determined in accordance with EN 374.

Since actual conditions of practical use often deviate from standardised conditions according EN 374 the glove manufacturer recommends to use the chemical protective glove in practice not longer than 50% of the recommended permeation time.

Manufacturer´s directions for use should be observed because of great diversity of types .

Suitable gloves tested according EN 374 are supplied e.g. from KCL GmbH, D-36124 Eichenzell, Vertrieb@kcl.de

##### *Eye protection:*

Safety goggles

##### *Skin and body protection:*

Wear suitable protective equipment.

Flame retardant antistatic protective clothing.

Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire.

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

### Environmental exposure controls

Handle in accordance with local environmental regulations and good industrial practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                              |  |
|------------------------------|--|
| Physical state               | : liquid   |
| Colour                       | : colourless   |
| Odour                        | : characteristic<br>fruity                                   |
| Melting point/range          | : -84 °C   |
| Boiling point/boiling range  | : 77 °C<br>at 1.013 hPa                                      |
| Flammability                 | : Not applicable   |
| Upper explosion limit        | : 11,5 %(V)  |
| Lower explosion limit        | : 2,1 %(V)   |
| Flash point                  | : -4 °C<br>Method: closed cup                                |
| Auto-ignition temperature    | : 427 °C   |
| Decomposition temperature    | : At normal pressure may be distilled without decomposition. |
| pH                           | : No data available  |
| Viscosity, kinematic         | : not determined   |
| Water solubility             | : ca. 80 g/l<br>at 20 °C                                     |
| Solubility in other solvents | : Soluble in most organic solvents                           |
| Partition coefficient: n-    | : log Pow 0,68   |

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

octanol/water

Vapour pressure : ca. 100 hPa  
at 20 °C

Vapour pressure : 379 hPa  
at 50 °C

Density : 0,902 g/cm<sup>3</sup>  
at 20 °C

Relative vapour density : ca. 3  
(Air = 1.0)

### 9.2 Other Information

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Viscosity, dynamic : ca. 0,45 mPa.s  
at 20 °C

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions.

### 10.2. Chemical stability

At normal pressure may be distilled without decomposition.

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### 10.4. Conditions to avoid

Keep away from heat and sources of ignition.  
Keep away from direct sunlight.

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

### 10.5. Incompatible materials

Vapours may form explosive mixtures with air.  
Plastic materials can be attacked.  
Explosive reactions with oxidising agents such as potassium chlorate and/or peroxides.

### 10.6. Hazardous decomposition products

Acetic acid  
Flammable gases/vapours

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

*Acute oral toxicity:*

LD50

Species: Rabbit

Value: 4.934 mg/kg

Method: OECD Test Guideline 401

*Acute dermal toxicity:*

LD50

Species: Rabbit

Value: > 18.000 mg/kg

*Acute inhalation toxicity:*

LC50

Species: Rat

Value: 56 mg/l

Exposure time: 4 h

*Skin irritation:*

Species: Rabbit

Classification: non-irritant

Method: OECD Test Guideline 404

*Eye irritation:*

Species: Rabbit

Classification: non-irritant

Method: OECD Test Guideline 405

*Respiratory or skin sensitisation:*

Species: Guinea pig

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

Classification: non-sensitizing  
Method: OECD Test Guideline 406

*Aspiration hazard:*  
No data available

### 11.2. Information on other hazards

Endocrine disrupting properties  
No data available

*Other information:*  
Not mutagenic in Ames Test  
Solvent vapours have a narcotic effect if inhaled in high concentrations.  
Solvents may degrease the skin.  
Prolonged skin contact may cause skin irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

*Toxicity to fish:*  
LC50  
Species: *Salmo gairdneri*  
Value: 230 mg/l  
Exposure time: 96 h

*Toxicity to aquatic plants:*  
NOEC  
Species: *Desmodesmus subspicatus* (green algae)  
Value: > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

EC50  
Species: *scenedesmus subspicatus*  
Value: 3.300 mg/l  
Exposure time: 48 h

*Toxicity to Microorganisms:*  
EC10  
Species: *Pseudomonas putida*

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

Value: 650 mg/l  
Exposure time: 16 h  
Method: DIN 38412

### *Toxicity to aquatic invertebrates:*

#### EC50

Species: Daphnia magna (Water flea)

Value: 3.090 mg/l

Exposure time: 24 h

Method: DIN 38412

#### NOEC

Species: Daphnia magna (Water flea)

Value: 2,4 mg/l

Exposure time: 21 d

### **12.2. Persistence and degradability**

#### *Biodegradability:*

Biodegradation: 100 %

Exposure time: 28 d

Result: Readily biodegradable.

Method: OECD 301 D

### **12.3. Bioaccumulative potential**

Bioaccumulation is unlikely.

### **12.4. Mobility in soil**

No data available

### **12.5. Results of PBT and vPvB assessment**

No data available

### **12.6. Endocrine disrupting properties**

No data available

### **12.7. Other adverse effects**

Biochemical Oxygen Demand (BOD) : Value: 293 mg/g

Chemical Oxygen Demand (COD) : Value: 1.816 mg/g

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

*Product:*

Dispose according to legal requirements.

*Packaging:*

Legal requirements are to be considered in regard of reuse or disposal of used packaging materials

*Further information:*

Provisions relating to waste:

EC Directive 2006/12/EC; 2008/98/EEC

Regulation No. 1013/2006

For personal protection see section 8.

### SECTION 14: Transport information

#### 14.1 UN number

ADR/RID:1173

IMDG:1173

IATA:1173

#### 14.2 UN proper shipping name

ADR/RID:ETHYL ACETATE

IMDG:ETHYL ACETATE

IATA:Ethyl acetate

#### 14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

#### 14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

#### 14.5 Environmental hazards

ADR/RID:no

Marine pollutant: no

#### 14.6 Special precautions for user

No data available

#### 14.7 Maritime transport in bulk according to IMO instruments

**Ethyl acetate**

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

No data available

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

| Basis  | Value   | Remarks  |
|--|---|--|
| Directive 2012/18/EC<br>SEVESO III<br>Listed in Regulation : P5c: FLAMMABLE LIQUIDS<br>Number in Regulation: 1.2.5.3 | <b>Quantity:</b> 5.000.000 kg<br><b>Quantity:</b> 50.000.000 kg |  |
| Substances of very high concern (SVHC)   |   | This product does not contain substances of very high concern according to Regulation (EC) No Article 57 above the respective regulatory 1907/2006 (REACH), concentration limit of $\geq 0.1\%$ (w/w). |

**Poison Control Center**

| Country        | Phone Number                 |
|----------------|------------------------------|
| Austria        | +4314064343                  |
| Belgium        | 070 245245                   |
| Bulgaria       | (+)35929154233               |
| Croatia        | (+3851)23-48-342             |
| Cyprus         | +357 2240 5611               |
| Czech Republic | +420224919293; +420224915402 |
| Denmark        | 82121212                     |
| Estonia        | 16662; (+372)6269390         |
| Finland        | 9471977                      |
| France         | +33(0)145425959              |
| Greece         | +30 210 779 3777             |
| Hungary        | (+36-80)201-199              |
| Iceland        | 5432222                      |

| Country         | Phone Number                               |
|-----------------|--|
| Liechtenstein   | +41 442515151                              |
| Lithuania       | +370532362052                              |
| Luxembourg      | 070245245; (+352)80002-5500                |
| Malta           | +356 2395 2000                             |
| Netherlands     | 030-2748888                                |
| Norway          | 22591300                                   |
| Poland          | +48 42 25 38 400                           |
| Portugal        | 800250250                                  |
| Romania         | +40 21 318 3606                            |
| Slovakia (NTIC) | +421 2 54 774 166                          |
| Slovenia        | +386 1 400 6051                            |
| Spain           | +34915620420                               |
| Sweden          | 112 (begär Giftninformation); +46104566786 |



**Ethyl acetate**

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

|                    |                        |                |                    |
|--------------------|------------------------|----------------|--------------------|
| Ireland            | +353(1)8092166         | Switzerland    | 145                |
| Italy              | 0382 24444             | United Kingdom | (+44) 844 892 0111 |
| Germany            | Berlin : 030/19240     |                |                    |
|                    | Bonn : 0228/19240      |                |                    |
|                    | Erfurt : 0361/730730   |                |                    |
|                    | Freiburg : 0761/19240  |                |                    |
|                    | Göttingen : 0551/19240 |                |                    |
|                    | Homburg : 06841/19240  |                |                    |
|                    | Mainz : 06131/19240    |                |                    |
| Munich : 089/19240 |                        |                |                    |
| Latvia             | +37167042473           |                |                    |

**Other inventory information**

US. Toxic Substances Control Act  
On TSCA Inventory

Australia. Inventory of Industrial Chemicals (AIIC), as amended  
On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)  
All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List  
On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI)  
On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS)  
On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC)  
On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand  
On the inventory, or in compliance with the inventory

## Ethyl acetate

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

Taiwan Chemical Substance Inventory (TCSI)  
On the inventory, or in compliance with the inventory

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

### Text of H-statements referred to under heading 3

ethyl acetate : H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.

### Further information

All directives and regulations refer to amended versions.  
Vertical lines in the left hand margin indicate a relevant amendment from the previous version.

#### Abbreviations:

EC European Community  
CAS Chemical Abstracts Service  
DNEL Derived no effect level  
PNEC Predicted no effect level  
vPvB Very persistent and very bioaccumulative substance  
PBT Persistent, bioaccumulative und toxic substance

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.

**Ethyl acetate**

33211-1L

Version 2.3

Revision Date 17.12.2022

Supersedes 1

---