

Pentane			
34956-2.5L			
Version 1.7		Revision Date 17.12.2022	
SECTION 1: Identification of t	he su	bstance/mixture and of the co	ompany/undertaking
1.1. Product identifier			
Product name	:	Pentane	
SDS-number	:	00000020211	
Type of product	:	Substance	
Remarks	:	SDS according to Art. 31 of Re In accordance to the Article 14 (EC) No 1907/2006, exposure characterisation is not required	(1) of the REACh Regulation estimation and risk
Chemical name	:	pentane	
Index-No.	:	601-006-00-1	
REACH Registration Number	:	no data available	
1.2. Relevant identified u	ises d	of the substance or mixture an	nd uses advised against
Use of the Substance/Mixture	:	Laboratory chemicals	
Uses advised against	:	none	
1.3. Details of the suppli	er of	the safety data sheet	
Company	:	Honeywell International Inc. 115 Tabor Road 07950-2546 Morris Plains USA	Honeywell International, Inc. 115 Tabor Road Morris Plains, NJ 07950-2546 USA
Telephone For further information, please contact:	:	SafetyDataSheet@Honeywell.	com
1.4. Emergency telephon	e nu	mber	
		Page 1 / 17	



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

Emergency telephone number Country based Poison Control Center : +1-703-527-3887 (ChemTrec-Transport) +1-303-389-1414 (Medical)
 : see chapter 15.1

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Flammable liquids Category 2 H225 Highly flammable liquid and vapour. Aspiration hazard Category 1 H304 May be fatal if swallowed and enters airways. Specific target organ toxicity - single exposure Category 3 - Central nervous system H336 May cause drowsiness or dizziness. Long-term (chronic) aquatic hazard Category 2 H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

REGULATION (EC) No 1272/2008

Hazard pictograms



Signal word	: Danger	
Hazard statements	: H225 H304	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways.
	H336 H411	May cause drowsiness or dizziness. Toxic to aquatic life with long lasting
	EUH066	effects. Repeated exposure may cause skin
Processitionary statements	: P210	dryness or cracking. Keep away from heat, hot surfaces,
Precautionary statements	. F210	sparks, open flames and other ignition sources. No smoking.
	P243	Take precautionary measures against static discharge.

Honeywell Riedel-de Haën[™]

Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

P260	Do not breathe dust/ fume/ gas/ mist/
P280	vapours/ spray. Wear protective gloves/ eye protection/
P301 + P330 + P331	face protection. IF SWALLOWED: Rinse mouth. Do
P304 + P340	NOT induce vomiting. IF INHALED: Remove person to fresh
	air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.

2.3. Other hazards

Take measures to prevent the build up of electrostatic charge. Results of PBT and vPvB assessment, see chapter 12.5.

SECTION 3: Composition/information on ingredients

3.1. Substance

Chemical name	CAS-No. Index-No. REACH Registration Number EC-No.	Classification 1272/2008	Concentration	Remarks
pentane	109-66-0 601-006-00-1 203-692-4	Flam. Liq. 2; H225 Asp. Tox. 1; H304 STOT SE 3; H336; Central nervous system Aquatic Chronic 2; H411 EUH066	100 %	

3.2. Mixture

Not applicable

Occupational Exposure Limit(s), if available, are listed in Section 8. For the full text of the H-Statements mentioned in this Section, see Section 16.

Page 3 / 17



:

Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice:

First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately. If unconscious, place in recovery position and seek medical advice.

Inhalation:

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Consult a physician.

Skin contact:

After contact with skin, wash immediately with plenty of water. Call a physician if irritation develops or persists.

Eye contact:

Rinse thoroughly with plenty of water, also under the eyelids. Protect unharmed eye. Consult a physician.

Ingestion:

When swallowed, allow water to be drunk. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

See Section 11 for more detailed information on health effects and symptoms.



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Water spray Foam Carbon dioxide (CO2) Dry powder

Extinguishing media which shall not be used for safety reasons: High volume water jet

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material. Pick for disposal in tightly closed containers

6.4. Reference to other sections

For personal protection see section 8.

Page 5 / 17



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling: Exhaust ventilation at the object is necessary.

Advice on protection against fire and explosion: Take precautionary measures against static discharges. Keep away from heat and sources of ignition. Keep away from direct sunlight.

Hygiene measures: General industrial hygiene practice.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

no additional data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits:

Components	Basis / Value type	Value / Form of exposure	Exceeding Factor	Remarks
pentane	EH40 WEL TWA	1.800 mg/m3 600 ppm		
pentane	EH40 WEL			Listed
pentane	EU ELV TWA	3.000 mg/m3 1.000 ppm		Indicative

TWA - Time weighted average

Page 6 / 17

Honeywell Riedel-de Haën™

Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

DNEL/ PNEC-Values

Component	End- use/impact	Exposure duration	Value	Exposure routes	Remarks
pentane	Workers / Long-term systemic effects		3000 mg/m3	Inhalation	
pentane	Workers / Long-term systemic effects		432mg/kg bw/d	Skin contact	
pentane	Consumers / Long-term systemic effects		643 mg/m3	Inhalation	
pentane	Consumers / Long-term systemic effects		214mg/kg bw/d	Skin contact	
pentane	Consumers / Long-term systemic effects		214mg/kg bw/d	Ingestion	

Component	Environmental compartment / Value	Remarks
pentane	Fresh water: 0,23 mg/l	
pentane	Marine water: 0,23 mg/l	
pentane	Sewage treatment plant: 3,6 mg/l	
pentane	Fresh water sediment: 1,2 mg/kg dw	
pentane	Marine sediment: 1,2 mg/kg dw	
pentane	Soil: 0,55 mg/kg dw	

Page 7 / 17



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

8.2. Exposure controls

Occupational exposure controls

The Personal Protective Equipment must be in accordance with EN standards:respirator EN 136, 140, 149; safety glasses EN 166; protective suit: EN 340, 463, 468, 943-1, 943-2; gloves EN 374, 511; safety shoes EN-ISO 20345. Do not breathe vapours/dust. Recommended preventive skin protection Take off all contaminated clothing immediately. Avoid contact with skin and eyes.

Personal protective equipment

Respiratory protection: Short term: filter apparatus, filter AX In the case of vapour formation use a respirator with an approved filter.

Hand protection: Glove material: Nitrile rubber Break through time: > 480 min Glove thickness: 0,4 mm Camatril® 730 Gloves must be inspected prior to use. Replace when worn. Remarks:Supplementary note: The specifications are based on information and tests from similar substances by analogy. Due to varying conditions (e.g.temperature or other strains) it must be considered that the usage of a chemical protective glove in practice may be much shorter than the permeation time determined in accordance with EN 374. Since actual conditions of practical use often deviate from standardised conditions according EN 374 the glove manufacturer reccomends to use the chemical protective glove in practice not longer than 50% of the recomended permeation time. Manufacturer's directions for use should be observed because of great diversity of types . Suitable gloves tested according EN 374 are supplied e.g. from KCL GmbH, D-36124 Eichenzell, Vertrieb@kcl.de Eye protection: Safety goggles

Skin and body protection: Protective suit



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

Environmental exposure controls

Handle in accordance with local environmental regulations and good industrial practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	characteristic
molecular weight	:	72,15 g/mol
Melting point/range	:	-131 °C
Boiling point/boiling range	:	36 - 37 °C
Upper explosion limit	:	8 %(V)
Lower explosion limit	:	1,4 %(V)
Flash point	:	-35 °C
Auto-ignition temperature	:	285 °C
Decomposition temperature	:	At normal pressure may be distilled without decomposition.
рН	:	Not applicable
Viscosity, kinematic	:	No data available
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	1.599 hPa at 50 °C
Vapour pressure	:	684 hPa
		Page 9 / 17



Pentane

34956-2.5L

Version 1.7	Revision Date 17.12.2022	
	at 25 °C	
Density	: 0,631 g/cm3 at 15 °C	
Relative vapour density	: No data available	
9.2 Other Information		
Evaporation rate	: No data available	
Viscosity, dynamic	: 0,25 mPa.s at 20 °C	

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

At normal pressure may be distilled without decomposition.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Keep away from heat and sources of ignition. Keep away from direct sunlight.

10.5. Incompatible materials

Formation of explosive gas/air mixtures.

10.6. Hazardous decomposition products

Page 10 / 17



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity: LD50 Species: Rat Value: > 2.000 mg/kg Method: OECD Test Guideline 401

Acute dermal toxicity: LD50 Species: Rabbit Value: 3.000 mg/kg

Acute inhalation toxicity: LC50 Species: Rat Value: 364 mg/l Exposure time: 4 h

Skin irritation: non-irritant

Eye irritation: non-irritant

Respiratory or skin sensitisation: No data available

Carcinogenicity: Species: not specified Note: No data available Germ cell mutagenicity: Note: No data available

Reproductive toxicity: Species: not specified Remarks: No data available

Aspiration hazard: May be fatal if swallowed and enters airways.

Page 11 / 17



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

11.2. Information on other hazards

Endocrine disrupting properties No data available

Other information: Solvent removes skin oil from the skin. Solvent vapours have a narcotic effect if inhaled in high concentrations. Irritating to skin and mucous membranes Not mutagenic in Ames Test

SECTION 12: Ecological information

12.1. Toxicity

Toxicity to fish: No data available

Toxicity to aquatic plants: EC50 Species: Algae Value: 1 mg/l Exposure time: 8 h

Toxicity to aquatic invertebrates: EC50 Species: Daphnia magna (Water flea) Value: 9,74 mg/l Exposure time: 48 h

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Page 12 / 17



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

Should not be released into the environment. Toxicity to fish Toxic to aquatic organisms. Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product: Dispose according to legal requirements.

Packaging:

Legal requirements are to be considered in regard of reuse or disposal of used packaging materials

Further information: Provisions relating to waste: EC Directive 2006/12/EC; 2008/98/EEC Regulation No. 1013/2006

For personal protection see section 8.

SECTION 14: Transport information

14.1 UN number ADR/RID:1265	IMDG:1265	IATA:1265
14.2 UN proper shipping name ADR/RID:PENTANES IMDG:PENTANES IATA:Pentanes		
14.3 Transport hazard class(es) ADR/RID: 3	IMDG: 3	IATA: 3
	Page 13 / 17	



Pentane 34956-2.5L Version 1.7 Revision Date 17.12.2022 14.4 Packaging group ADR/RID: II IMDG: II IADR/RID: II IMDG: II IATA: II 14.5 Environmental hazards ADR/RID: yes Marine pollutant: yes 14.6 Special precautions for user No data available 14.7 Maritime transport in bulk according to IMO instruments No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Basis	Value	Remarks
Directive 2012/18/EC Listed in Regulation : P5c: FLAMMABLE LIQUIDS	Quantity : 5.000.000 kg Quantity : 50.000.000 kg	
Directive 2012/18/EC Listed in Regulation : E2: Hazardous to the Aquatic Environment	Quantity : 200.000 kg Quantity : 500.000 kg	
Substances of very high concern (SVHC)		This product does not contain substances of very high concern according to Regulation (EC) No Article 57 above the respective regulatory 1907/2006 (REACH), concentration limit of \ge 0.1 % (w/w).

Poison Control Center

Country	Phone Number	Country	Phone Number
Austria	+4314064343	Liechtenstein	+41 442515151
Belgium	070 245245	Lithuania	+370532362052
Bulgaria	(+)35929154233	Luxembourg	070245245; (+352)80002-5500

Page 14 / 17



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

1	1
Croatia	(+3851)23-48-342
Cyprus	+357 2240 5611
Czech Republic	+420224919293; +420224915402
Denmark	82121212
Estonia	16662; (+372)6269390
Finland	9471977
France	+33(0)145425959
Greece	+30 210 779 3777
Hungary	(+36-80)201-199
Iceland	5432222
Ireland	+353(1)8092166
Italy	0382 24444
	Berlin : 030/19240
	Bonn : 0228/19240
Germany	Erfurt : 0361/730730
	Freiburg : 0761/19240
	Göttingen : 0551/19240
	Homburg : 06841/19240
	Mainz : 06131/19240
	Munich : 089/19240
Latvia	+37167042473

Malta	+356 2395 2000
Netherlands	030-2748888
Norway	22591300
Poland	+48 42 25 38 400
Portugal	800250250
Romania	+40 21 318 3606
Slovakia (NTIC)	+421 2 54 774 166
Slovenia	+386 1 400 6051
Spain	+34915620420
Sweden	112 (begär Giftinformation);+46104566786
Switzerland	145
United Kingdom	(+44) 844 892 0111

Other inventory information

US. Toxic Substances Control Act On TSCA Inventory

Australia. Inventory of Industrial Chemicals (AIIC), as amended On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List

Page 15 / 17



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS) On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC) On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory (TCSI) On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Text of H-statements referred to under heading 3

pentane

:	H225	Highly flammable liquid and vapour.
	H304	May be fatal if swallowed and enters airways.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.
	EUH06	66 Repeated exposure may cause skin dryness or
	crackir	ng.

Further information

All directives and regulations refer to amended versions. Vertical lines in the left hand margin indicate a relevant amendment from the previous version.

Abbreviations: EC European Community

Page 16 / 17



Pentane

34956-2.5L

Version 1.7

Revision Date 17.12.2022

CAS Chemical Abstracts Service DNEL Derived no effect level PNEC Predicted no effect level vPvB Very persistent and very biaccumulative substance PBT Persistent, bioaccmulative und toxic substance

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.

Page 17 / 17