CORNING	Life Sciences	Document Number: LSR00053	Rev.: <b>5</b>
Description (Class): Reference, Customer Technical Data Sheet – Round Bottom Tubes, 5 mL PP, no cap		Page: <b>1 of 2</b>	

#### **APPLICATIONS:**

- Dilution of samples or solutions
- Molecular biology: e.g. centrifugation or pelleting of bacterial cells for DNA isolation; purification and precipitation of nucleic acids.
- Bacterial culture (352053 only cap available separately)
- Sample storage (cap available separately)
- Chromatography fraction collection
- Centrifugation of precipitates

#### **FEATURES:**

## Strong, clarified polypropylene

- Chemically resistant to alcohols and mild organic solvents (not recommended for extraction procedures).
- Hydrophobic, biologically inert surface for good cell or protein recovery.
- Clear wall permits easy viewing of tube contents.
- Stable from -80°C to +121°C
- · Can withstand centrifugal forces up to 3000 rcf

#### Convenient bulk packaging

#### STERILITY:

352002: Non-sterile

352053: Product is gamma irradiated

### **REGULATORY COMPLIANCE:**

Falcon® products are manufactured under the current ISO 9001 and the current FDA Quality System Regulation 21 CFR Section 820.

## RESTRICTIONS:

- Refer to Centrifuge Tube Chemical Resistance Chart at: http://catalog2.corning.com/Lifesciences/media/pdf/an\_DL\_082\_Falcon\_Tube\_Pipet\_Cultureware\_Chemic al\_Resistance\_Chart.pdf
- Refer to "Thermoplastics Properties Chart," available at: http://catalog2.corning.com/Lifesciences/media/pdf/an\_DL\_226\_Falcon\_ThermoPlastics\_Broch.pdf

	CORNING	Life Sciences	Document Number: LSR00053	Rev.: <b>5</b>	
Description (Class): Reference, Customer Technical Data Sheet – Round Bottom Tubes, 5 mL PP, no cap		Page: <b>2 of 2</b>			

Material: Clarified Polypropylene

**Related Catalog Numbers:** 

Cat. No.Packout DescriptionCapSterileGraduations3520021000/Bag, 1000/CaseNoneNoneNone352053125/Bag, 1000/CaseNoneYesNone

# **Dimensions = mm (inches)**

**TUBE** A = 73.79 (2.905)


**B** = O.D. 12.40 (.488) **C** = O.D. 11.43 (.450)

Top I.D. at rim = 10.62 (.418)
Depth of rim = 3.05 (.120)
Top I.D. at chamfer = 10.49 (.413)
Bottom I. D. (Sph. Diameter) = 8.99 (.354)

Wall thickness = 1.27 (.050) at the sides

Nominal volume = 5 mLRCF ratings = 3,000 g/s

Chem. Compatibility: See Chemical Resistance Chart



Warranty/Disclaimer: Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures.