

CORNING	Life Sciences	Document Number: LSR00039	Rev.: 9
Description (Class): Falcon® Conical Centrifuge Tubes, 15mL PP			Page: 1 of 2

APPLICATIONS:

- Cell centrifugation: pelleting; separation by density gradients.
- Molecular biology: e.g. Concentrating bacteria for DNA isolation; purification and precipitation of nucleic acids.
- Sample storage (ambient temperature or frozen).
- Centrifugation of precipitates.

FEATURES:

Strong, clarified polypropylene

- Chemically resistant to alcohols and mild organic solvents (not recommended for extraction procedures).
- Hydrophobic, biologically inert surface for good cell or protein recovery.
- Translucent wall permits easy viewing of tube contents.
- Stable from -80°C to +121°C.
- Tested to withstand centrifugation of 12,000 RCF in a fully supported rotor with room temperature water. See rotor guide in product catalog or online at corning.com/lifesciences for specific test conditions and additional guidance on high speed centrifugation.

Conical Design

- Fits most standard floor model and table-top centrifuges, including many biohazard contained models.

Dome seal screw on closure

- Biologically inert, high density polyethylene provides a chemically resistant surface.
- Double threaded to reduce cross-threading.
- Interface/plug sealing ring retains liquid during routine laboratory procedures.

Dark blue graduations in 0.5mL increments

- Plainly visible with either clear or turbid samples.
- Solvent resistant printing will not rub off.

White writing area

- Facilitates sample identification.
- Solvent resistant - will not rub off during routine laboratory procedures.
- Compatible with Sharpie® marker.

Available in racked or bulk packaging configurations

- Recyclable polystyrene racks offer convenience of oriented product presentation.
 - Racks include viewing window slots, so samples can be viewed without removing tubes from rack.
 - Rack positions are numbered for easy identification of tube locations.
 - Racks are easily stackable.
- Bulk packaging uses 40% less packaging material, an environmentally friendly alternative.
- Both configurations feature a medical-grade, peel-open format for aseptic presentation of sterile tubes.

STERILITY:

Product is gamma irradiated and dosimetrically based upon U.S. Association for the Advancement of Medical Instrumentation (AAMI) recommended practices in effect at the time of validation. Sterilization records are reviewed and signed off by qualified personnel for product release.

Warranty/Disclaimer: Unless otherwise specified, all products are For Research Use Only. Not intended for use in diagnostic or therapeutic procedures.

For a listing of trademarks, visit www.corning.com/lifesciences/trademarks.

© 2013 Corning Incorporated

All other trademarks in this document are the property of their respective owners.

CORNING	Life Sciences	Document Number: LSR00039	Rev.: 9
Description (Class): Falcon® Conical Centrifuge Tubes, 15mL PP			Page: 2 of 2

FDA COMPLIANCE:

Falcon products are manufactured under the ISO 9001:2008 Standard, and the current FDA Quality System Regulation in Chapter 1, Title 21, Section 820 of the Code of USA Federal Regulations.

RESTRICTIONS:

Refer to Centrifuge Tube Chemical Resistance Chart and Thermoplastics Properties Chart, available via the Internet at corning.com/lifesciences.

Material: Clarified Polypropylene

Related Catalog Numbers:

Cat No.	Packout/Description	Cap	Sterile	Graduations	Wr. Patch	Rack
352096	50/Bag, 500/Case	Dome-seal	Yes	Printed	Yes	No
352097	50/Rack, 500/Case	Dome-seal	Yes	Printed	Yes	Yes
352196	50/Bag, 500/Case	Dome-seal	Yes	Printed	Yes	Yes

Dimensions = mm (inches)


TUBE

A = 118.8 (4.68)
B = O.D. 17.37 (.684)
C = O.D. 15.75 (.620)
D = 22.48 (.885)

Tube height w/cap = 120.75 (4.754)
Top I.D. at rim = 14.66 (.577)
O.D. at thread = 19.25 (.758)
Bottom O. D. (Sph. Dia.) = 3.18 (.125)
Bottom angle = 26.92 degrees
Min. wall thickness = .76 (.030)
Nominal volume = 15mL
RCF ratings = 12,000xg
Chem. Compatibility: See Cat. Resistance Chart
Threads to fit special cap design.

CAP 20mm Threaded Dome Seal Closure
Material: Blue HDPE
E = 10.41 (.410)
F = O.D. 22.98 (.905)

I.D. (bottom) = 19.91 (.784)
Threads are designed to fit Falcon® tubes only.



Warranty/Disclaimer: Unless otherwise specified, all products are For Research Use Only. Not intended for use in diagnostic or therapeutic procedures.

For a listing of trademarks, visit www.corning.com/lifesciences/trademarks.
© 2013 Corning Incorporated
All other trademarks in this document are the property of their respective owners.