



Technical data sheet

Item code PL 602B

TECHNICAL SPECIFICATIONS

Description:	Stackable crate Bottom Closed Walls Closed Handles Closed
Raw material:	High density polyethylene (HDPE)
Usage:	Multipurpose container designed for handling and storage of bulk goods. Perfect for almost any industry, it is particularly suitable for pharmaceutical, chemical, logistics and transport companies. Non deformable and very stable it withstands even at heavy loads. It resists to thermal shock and corrosive chemicals.

DIMENSIONS

Capacity:	20 l
Internal dimensions:	380x280x195 mm
External dimensions:	440x315x200 mm
Weight:	1,07 kg
Dimensional tolerances:	± 3%



GENERAL FEATURES

Semi transparent:	No
Colour:	White
Load capacity	-
Stackable load	-
Dynamic load	-
Temperature range:	-40°C / + 80°C
Autoclavable:	No
Sterilizable:	By radiation
Conformity with standards:	-
Food contact compliance:	The product is suitable for food contact. It meets regulatory requirements of 1935/2004/CE, UE 10/2011 and following amendmends.



Technical data sheet

Item code PL 602B

PACKAGING

Pieces per bag (MOQ):	1		
Pieces per box:	-		
Pieces per pallet	66	Pallet dimensions	80x120x220 cm

REMARKS / OPTIONAL ACCESSORIES

-

CHEMICAL COMPATIBILITY

Products manufactured by polyethylene or polypropylene are normally suitable for room-temperature contact with many organic solvents, diluted solutions of acids, bases and salts. They are typically not suitable for use with concentrated oxidizing acids and halogenated solvents. Detailed information on physical properties and chemical resistance (including concentration and temperature effect) are available upon request.

Several factors however may effect chemical compatibility such as temperature, concentration, contact time, presence of internal stress, wall/film thickness. The user is advised to carry out its own tests to determine product suitability for the particular environment/application.

STORAGE CONDITIONS

Storage area should be clean and dry, odor free, possibly equipped with pest control system. Product should be stored in its original sealed packaging, always protect from dust. Never place packaging on the floor. Use instead raised surfaces such as pallets or shelves. Optimum storage temperature is between 10°C and 30°C, 20% to 80% RH. Never exceed the following limits: -10°C / +40°C. Never expose product to direct sunlight.

LEGAL DISCLAIMER

The information contained in this data sheet are intended for informational purposes only and may be modified without notice. The images are for illustrative purposes and may differ from the actual product. Lamaplast Srl reserves the right to make improvements and / or changes to the product described without notice.