


Trade name	<b>"T" untapered connectors</b>
Use	Useful for any tubing system and vacuum line
Material	Polypropylene PP



#### TECHNICAL FEATURES

External diameter	mm. 16,00
Valley diameter	mm. 14,70
Crest diameter	mm. 15,60
Hole diameter	mm. 12,10
General dimensional tolerance	mm. +/- 0,2
Other features	Excellent chemical and temperature resistance. With serrations to hold hoses tightly and prevent slipping.

#### GENERAL FEATURES

CE Mark	Yes
Foodstuff suitability	EEC 90/128 92/39 – FDA 21 CFR 177.1520
Sterility	The product is NOT sterile but can be sterilized by radiations
Autoclavability	Yes

#### CHEMICAL RESISTANCE

Categories of substances	Reference	Concen. %	T. 20°	T. 40°	T.° 60
Inorganic acid	Sulphuric acid	98	B	C	-
Organic acid	Benzoic acid	100	A	B	B
Alcohol	Ethanol	100	A	A	A
Aldehydes	Acetaldehyde	100	B	C	-
Inorganic alkali	Sodium hydroxide	50	A	A	A
Organic alkali	Aniline	100	A	B	C
Ketone	Acetone	100	A	A	-
Esther	Ethyl acetate	100	B	B	C
Hydrocarbons, halogenated	Dichloroethylene	100	C	-	-
Hydrocarbons, aromatic	Benzene	100	B	C	-
Hydrocarbons, linear	Hexane	100	B	B	C
Supersolvent	Tetrahydrofuran	100	B	B	C

**Legenda** (not applicable if neglected):

- **A: fair resistance;** exposure (30 days) to the chemical does not cause any damage.
  - **B: sufficient resistance;** exposure causes damage of poor importance, which sometimes is only temporary.
  - **C: poor resistance;** exposure to chemical is not allowed, or causes immediate permanent damage.
- Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing..

#### PACKAGING

Case	Available in packagings of 100
------	--------------------------------

**Quality Assurance**  
Massimiliano Capitanio

**TECHNICAL FEATURES**

Trade name	<b>"T" untapered connectors</b>
Use	Useful for any tubing system and vacuum line
Material	Polypropylene PP

**DIMENSIONAL FEATURES**

External diameter	mm. 16,00
Valley diameter	mm. 14,70
Crest diameter	mm. 15,60
Hole diameter	mm. 12,10
General dimensional tolerance	mm. +/- 0,2
Other features	Excellent chemical and temperature resistance. With serrations to hold hoses tightly and prevent slipping.



**GENERAL FEATURES**

CE Mark	Yes
Foodstuff suitability	EEC 90/128 92/39 – FDA 21 CFR 177.1520
Sterility	The product is NOT sterile but can be sterilized by radiations
Autoclavability	Yes

**CHEMICAL RESISTANCE**

Categories of substances	Reference	Concen. %	T. 20°	T. 40°	T.° 60
Inorganic acid	Sulphuric acid	98	B	C	-
Organic acid	Benzoic acid	100	A	B	B
Alcohol	Ethanol	100	A	A	A
Aldehydes	Acetaldehyde	100	B	C	-
Inorganic alkali	Sodium hydroxide	50	A	A	A
Organic alkali	Aniline	100	A	B	C
Ketone	Acetone	100	A	A	-
Esther	Ethyl acetate	100	B	B	C
Hydrocarbons, halogenated	Dichloroethylene	100	C	-	-
Hydrocarbons, aromatic	Benzene	100	B	C	-
Hydrocarbons, linear	Hexane	100	B	B	C
Supersolvent	Tetrahydrofuran	100	B	B	C

**Legenda** (not applicable if neglected):

- **A: fair resistance;** exposure (30 days) to the chemical does not cause any damage.
- **B: sufficient resistance;** exposure causes damage of poor importance, which sometimes is only temporary.
- **C: poor resistance;** exposure to chemical is not allowed, or causes immediate permanent damage.

Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing..

**PACKAGING**

Case	Available in packagings of 10
------	-------------------------------

**Quality Assurance**  
Massimiliano Capitano

**DOMINIQUE DUTSHER SAS**