VIF Digital Thermoregulator

The Innovative Vertex Digital Thermoregulator

- Timer function, unique on the market
- Automatic shut down of the thermoregulation
- Friendly handling of probe position



The digital thermoregulator **VERTEX VTF** is equipped with innovative **FUZZY LOGIC technology** that allows better alignment with the set point temperature (± 0,5°C) and lower initial "overshoot" (initial discrepancy with the set temperature) in spite of the "traditional" technologies available on the market.

Among the main characteristics, VERTEX VTF has a **highly automated programming** and checking of the liquid's temperature (-10°...+300°C) and **digital timer** with automatic shutdown of the thermoregulation.

VERTEX VTF can be used in combination with most common magnetic stirrers that have the option to connect to a contact thermometers and various heating apparatus (e.g. water and oil baths, heating plates, thermomantles, etc.) connected to the accessory PW10.

For an optimal solution, VELP suggests the use of VERTEX VTF with the heating magnetic stirrers type **AREX** and **AREC.X**, which are designed to work with the contact thermometers.



VELP System: everything in only one piece

VTF is provided with a VELP system for clamping on rods without the need of clamps and **for handling / positioning** of the probe inside the liquid in a **very easy way**.



| Technical Data Desc | cription |
|---|--------------------------------|
| | |
| Construction material: tech | nnopolymer |
| Stainless steel probe type Pt 100: 250 | mm length and Ø 3 mm |
| Clamping on road: from | n Ø 10 to 13 mm |
| Display: LCD |) |
| Protection rating CEI EN 60529: IP 5 | 54 |
| Thermoregulation range: -10. | +300°C |
| Precision: ± 0, | 5°C |
| Resolution: 0,2° | °C |
| Working time: from | n 00:00 to 24:59 (h:min) |
| Remaining time reading: pos | sible |
| Visualization of the maximum temperature reached: pos | sible |
| Power supply: 12V | / cc |
| Weight: 0,3 | Kg (0.7 lb) |
| Dimension (WxHxD): 75x | 145x120 mm (3x5,7x4,7 in) |
| Ordering information Description | cription |
| F208B0063 VTF | Vertex Digital Thermoregulator |
| A00000001 Deri | ivation element PW10 |
| A00000002 Prol | be extension cable, 1m lenght |
| A00000003 Glas | ss probe |
| A00000004 Clar | mp for the probe |

Your authorized agent:

We reserve the right to make technical alternations We do not assume liability for errors in printing, typing or transmission







