



Scilabub Limited, 9 Huntingdon Court, Measham, Derbyshire, DE12 7NQ, UK.


T: +44 (0) 1530 279996 <http://www.scilabub.com> email: sales@scilabub.com

Information for customer: FROSTERS Aprons & Gaiter

APRON & GAITER DESCRIPTION

The outer layer, of royal blue, woven, polyamide, has a waterproof coating to resist condensed water on cold surfaces. The middle layer is of special polyolefin/polyester micro fibre, which is almost twice as effective in thermal insulation as a similar thickness of down. This minimises heat transfer without being so thick as to be cumbersome. The inner layer is of cotton for comfortable wear.

Stockcode	Style No	Style Ref	Size	Chest/cm	Length/cm
4431000080	SPA/194	APR/CMS	Small	80-120	90
4431000090	SPA/194	APR/CMM	Medium	80-120	100
4431000100	SPA/194	APR/CML	Large	80-120	120
4431000110	SPA/194	APR/CMXL	XL	80-120	140
1991940021	13P/2471	GAITER	STD		



Length/cm



CE 0598

UK CA 0120

WARNINGS:

These aprons & gaiter may lose their insulative properties when wet and when wet inside so always keep the inner dry when wearing the & gaiter. Guidance on maximum permissible exposure time to cold temperatures is given in Annex B of EN 511:2006. These aprons & gaiter have been specifically designed for use when handling non-flammable liquid gas and the user should not be exposed to the low temperatures for sustained periods.

Test results apply to the aprons & gaiter in the as received condition and may differ if cleaned. Do not use near moving machinery due to entanglement hazard. Overall classification may not reflect the performance of only the outermost layer. These aprons & gaiter are not suitable for protection against sharply pointed objects such as hypodermic needles.

MARKING

Each packet shall be labelled / contain the appropriate marking with regards to the amount, type, size, manufacturer, performance levels and mark. Labels on the clothing will contain similar information. This information will be provided in the minimum resale quantity.

STANDARD EN 388:2016

Abrasion	Resistance	2
Cut	Resistance	X
Cut	Resistance (TDM)	X
Tear	Resistance	2
Puncture	Resistance	X

EN 511:2006

Flexibility	Pass
Water Penetration**	X
Extreme Cold Flexibility	Pass
Convective Cold	2
Contact Cold	2

Level

2
X
X
2
X
Pass
X
Pass
2
2



(**The water penetration test does not apply to this style they should not be get wet on the inside or immersed in liquids as this may lead to a reduction in the insulative properties of the aprons & gaiter.)

These aprons & gaiter have been specifically designed for use when handling non-flammable liquid gas and the user should not be exposed to the low temperatures for sustained periods. Aprons & gaiter should not be worn where there is a risk of entanglement with moving parts of machines. The performance may not reflect the performance of the outermost layer. Damaged aprons & gaiter will not offer the same level of performance and should be replaced.

COMPLEX SAFETY CATERGORY

Aprons & gaiter are designed to protect the torso and lower legs in the working environment in accordance with BS EN ISO 13688: 2013 and EN 511 and related standards have been used as currently this no suitable standard for this product and satisfies the basic requirements of the PPE Regulation 2016/425 on personal protective equipment, and as amended to apply in GB. When selecting an apron & gaiter based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above. None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

CARE / MAINTENANCE

Cleaning and disinfection is not intended for these items. Both new and used items should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged aprons & gaiters should not be worn and should be disposed of. Wet or contaminated aprons & gaiters should not be used. Dirty aprons may not provide the same level of protection as that shown. Aprons & gaiter should not be left in a contaminated condition if re-use is intended, in which case aprons & gaiter should be cleaned as far as possible, provided no serious hazards exist, before removal. Excess contaminant should first be removed, e.g. loose dirt can be brushed off with a soft brush. The aprons may be de-contaminated with mild detergent solution, then rinsed with clean water and allowed to dry naturally, ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable that the aprons are removed without the contaminant contacting the bare hands. Washing is not recommended. Do not wring. Do not tumble dry. Do not use bleach. Aprons & gaiter may be rinsed in water and allowed to drip dry in ambient temperatures. Reshape whilst still damp.

Warning:

PACKING AND STORAGE

Can be used under normal climatic conditions. Aprons & gaiter shall be wrapped in polymeric packaging. Aprons and gaiter can be used up to five years after date of supply if stored correctly. Store in original packaging. Aprons should be ideally stored in a cool dry place away from direct sunlight at ambient temperatures (between 5°C and 25°C) in a dry well ventilated area in original packaging to maintain the optimum properties of the apron. The aprons are packed in bundles, along with this leaflet. This bundle is suitable for transportation and storage.

OBSOLESCENCE Stored correctly, the aprons' physical properties will not change for up to five years.

GENERAL The quality systems used to manufacture the aprons are in compliance with ISO 9001:2015.

PLEASE NOTE The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection; however, it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitable for the intended use.

DECLARATION Scilabub declares that the new PPE as described in the TD 1048 technical specification for the following Aprons & Gaiters, are in conformity with provisions of PPE Regulation 2016/425 on personal protective equipment, and as amended to apply in GB Module D, and using the national standard transposing harmonised standard No :BS EN 388:2016,BS EN 511:2006, BSEN 21420:2020, and identical to the PPE which is the subject of the UKCA certificate LECFI00385152 issued by:ITS TESTING SERVICES, CENTRE COURT, MERIDAN BUSINESS PARK, LEICESTER, U.K., LE19 1 WD, Approved Body Number: AB0362 who performed the type-examination and is subject to the procedure set out in the UK legislation UK under the supervision of the approved body SGS United Kingdom, Rossmore Business Park, Ellesmere Port, South Wirral, Cheshire, CH65 3EN,United Kingdom.Their approved body number is 0120 and is also the subject of the EU certificate. No: ITASLNB21022720 issued by:. Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy NB 2575, and is subject to the procedures under the supervision of the notified body SGS Fimko Oy, Takomotie 8, Helsinki, 00380, Finland0598. Their notified body number is 0598.

.Done at : Scilabub Limited, Measham, Derbyshire, on 16/09/22

Signature: Mr M. Gee. Managing Director

This series satisfies the basic requirements of the PPE Regulation (EU) 2016/425 in being innocuous/free from nuisance factors, ergonomic and breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified.

Further information is available at the below address:

Scilabub Limited

9 Huntingdon Court, Measham, Derbyshire, DE12 7NQ, UK.
T: +44 (0)1530 279996 <http://www.scilabub.com> email: sales@scilabub.com