FICHE TECHNIQUE

GRADE FQ30

DESIGNATION

- Filtres en microfibres de quartz
- Liant : aucun
- Hydrophobe

APPLICATIONS

- Mesure des émissions des cheminées, sorties de gaz de combustion et aérosols
- Analyse des gaz acides (sauf fluorure d'hydrogène)
- Contrôle du plomb en suspension dans l'atmosphère

SPECIFICATIONS TECHNIQUES

CARACTERISTIQUES	VALEURS	UNITE	NORMES
Grammage	85	g/m²	DIN 53104
Epaisseur	0.43	mm	
Porosité	1.5	µm	
Vitesse de filtration	60	sec	DIN 53137
Efficacité de rétention	99.999	%	
Résistance à la chaleur	≤ 900	°C	

DONNEES COMMERCIALES

- Disponibles en disques à plat (A), en boîte de 50 filtres

DOMINIQUE DUTSCHER SAS

TECHNICAL DATA

GRADE FQ30

DESCRIPTION

- Quartz microfibers filters
- Binder: none
- Hydrophobic

APPLICATIONS

- Emission control of chimney smokes, combustion gas outlets and aerosols
- Analysis of acid gases (except hydrogen fluoride)
- Control of suspended lead particles in air

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	VALUES	UNITS	STANDARDS
Weight	85	g/m²	DIN 53104
Thickness	0.43	mm	
Pore size	1.5	µm	
Filtration speed	60	sec	DIN 53137
Retention efficiency	99.999	%	
Heat resistance	≤ 900	°C	

SALES DATA

- Available in plain discs (A), in box of 50 filters

DOMINIQUE DUTSCHER SAS