# FICHE TECHNIQUE

## GRADE FT306

### DESIGNATION

- Plaque filtrante
- Matière : cellulose, kieselguhr
- Liant : agent polyamide approuvé FDA

### APPLICATIONS

- Procédés industriels : cosmétique, pharmaceutique, agro-alimentaires, chimie…
- Clarification
- Filtration dégrossissante de la cire, vins blancs, rouges et rosés, apéritifs, vins pétillants
- Filtration clarifiante des produits photo-réactifs, liquides visqueux, huiles d'olive, sirops de sucre, jus de raisin, spiritueux

### SPECIFICATIONS TECHNIQUES

| CARACTERISTIQUES | VALEURS | UNITES |
|---|---|---|
| Grammage | 1100 | $g/m^2$ |
| Epaisseur | 2.9 | mm |
| Porosité | 3.0-8.0 | µm |
| Porosité max. | 19 | µm |
| Perméabilité | 314 | $L/m^2/mm$ |

### DONNEES COMMERCIALES

- Disponibles avec ou sans trous en disques à plat (A) ou en feuilles (F) ou en modules lenticulaires

DOMINIQUE DUTSCHER SAS

# TECHNICAL DATA

## GRADE FT306

### DESCRIPTION

- Filter sheets
- Material: cellulose, kieselguhr
- Binder: FDA approved polyamide agent

### APPLICATIONS

- Industrial applications: cosmetics, pharmaceuticals, foods, chemicals…
- Clarification
- Coarse filtration of wax, white, red and rose wines, aperitifs, sparkling wines
- Clarifying filtration of photo-reactive products, viscous liquids, olive oils, sugar syrups, grape juice, spirits

### TECHNICAL SPECIFICATIONS

| CHARACTERISTICS | VALUES | UNITS |
|---|---|---|
| Weight | 1100 | $g/m^2$ |
| Thickness | 2.9 | mm |
| Pore size | 3.0-8.0 | µm |
| Max. pore size | 19 | µm |
| Permeability | 314 | $L/m^2/mm$ |

### SALES DATA

- Available with or without holes in plain discs (A) or in sheets (F) or in lenticular modules

DOMINIQUE DUTSCHER SAS