FICHE TECHNIQUE

GRADE QT43

DESIGNATION

- Papier filtre quantitatif moyen (sans cendre)
- Matière : 100% cellulose
- Ruban rouge

APPLICATIONS

- Industries chimique, agroalimentaire, des boissons
- Analyses atmosphériques
- Analyses des sols
- Phosphate ammoniacé de magnésie, chromate de baryte et de plomb, oxalate de chaux…

SPECIFICATIONS TECHNIQUES

CARACTERISTIQUES	VALEURS	UNITE	NORMES
Poids	84	g/m²	DIN 53104
Épaisseur	0.2	mm	
Porosité	14-18	µm	
Vitesse de filtration	55	sec.	DIN 53137
Résistance à l'éclatement	0.2	kg/cm²	
Taux de cendres	<0.01	%	DIN 53138

DONNEES COMMERCIALES

Disponibles en :

- Feuilles : F
- Disques à plat : A
- Disques plissés : P

DOMINIQUE DUTSCHER SAS

TECHNICAL DATA

GRADE QT43

DESCRIPTION

- Medium quantitative filter paper (ashless)
- Material: 100% cellulose
- Red ribbon

APPLICATIONS

- Chemical, food and beverage industries
- Atmospheric analysis
- Soil analysis
- Ammonium phosphate of magnesia, barium and lead chromate, lime oxalate...

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	VALUES	UNITS	STANDARDS
Weight	84	g/m²	DIN 53104
Thickness	0.2	mm	
Pore size	14-18	µm	
Filtration speed	55	sec.	DIN 53137
Burst strength	0.2	kg/cm²	
Ash rate	<0.01	%	DIN 53138

SALES INFORMATION

Available in:

- Sheets: F
- Plain discs: A
- Folded discs: P

DOMINIQUE DUTSCHER SAS