FICHE TECHNIQUE

GRADE QT44

DESIGNATION

- Papier filtre quantitatif lent (sans cendre)
- Matière : 100% cellulose
- Ruban vert

APPLICATIONS

- Industries chimique, agroalimentaire, des boissons
- Analyses atmosphériques
- Analyses des sols
- Sulfate de baryum et de plomb, fluorure de calcium, sulfites de zinc et de nickel…

SPECIFICATIONS TECHNIQUES

CARACTERISTIQUES	VALEURS	UNITE	NORMES
Poids	74	g/m²	DIN 53104
Épaisseur	0.16	mm	
Porosité	7-9	µm	
Vitesse de filtration	100	sec.	DIN 53137
Résistance à l'éclatement	0.2	kg/cm²	
Taux de cendres	<0.01	%	DIN 53138

DONNEES COMMERCIALES

Disponibles en :

- Feuilles : F
- Disques à plat : A
- Disques plissés : P

DOMINIQUE DUTSCHER SAS

TECHNICAL DATA

GRADE QT44

DESCRIPTION

- Slow quantitative filter paper (ashless)
- Material: 100% cellulose
- Green ribbon

APPLICATIONS

- Chemical, food and beverage industries
- Atmospheric analysis
- Soil analysis
- Barium and lead sulphate, calcium fluoride, zinc and nickel sulphites…

TECHNICAL SPECIFICATIONS

CARACTERISTIQUES	VALEURS	UNITE	NORMES
Weight	74	g/m²	DIN 53104
Thickness	0.16	mm	
Filtration speed	7-9	sec.	DIN 53137
Pore size	100	µm	
Burst strength	0.2	kg/cm²	
Ash rate	<0.01	%	DIN 53138

SALES INFORMATION

Available in:

- Sheets: F
- Plain discs: A
- Folded discs: P

DOMINIQUE DUTSCHER SAS