FICHE TECHNIQUE

GRADE QT45

DESIGNATION

- Papier filtre quantitatif très lent (sans cendre)
- Matière : 100% cellulose
- Ruban bleu

APPLICATIONS

- Industries chimique, agroalimentaire, des boissons
- Analyses atmosphériques
- Analyses des sols
- Sulfate de baryum (à froid), acide de métazine, oxyde de cuivre, …

SPECIFICATIONS TECHNIQUES

CARACTERISTIQUES	VALEURS	UNITE	NORMES
Poids	84	g/m²	DIN 53104
Epaisseur	0.17	mm	
Porosité	2-4	µm	
Vitesse de filtration	140	sec.	DIN 53137
Résistance à l'éclatement	0.2	kg/cm²	
Taux de cendres	<0.01	%	DIN 53138

DONNEES COMMERCIALES

Disponibles en :

- Feuilles : F
- Disques à plat : A
- Disques plissés : P

DOMINIQUE DUTSCHER SAS

TECHNICAL DATA

GRADE QT45

DESCRIPTION

- Very slow quantitative filter paper (ashless)
- Material: 100% cellulose
- Blue ribbon

APPLICATIONS

- Chemical, food and beverage industries
- Atmospheric analysis
- Soil analysis
- Iron and aluminium hydroxide, most metal sulphites...

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	VALUES	UNITS	STANDARDS
Weight	84	g/m²	DIN 53104
Thickness	0.17	mm	
Filtration speed	2-4	sec.	DIN 53137
Pore size	140	µm	
Burst strength	0.2	kg/cm²	
Ash rate	<0.01	%	DIN 53138

SALES INFORMATION

Available in:

- Sheets: F
- Plain discs: A
- Folded discs: P

DOMINIQUE DUTSCHER SAS