FICHE TECHNIQUE

GRADE QT55

DESIGNATION

- Papier filtre quantitatif renforcé très lent (sans cendre)
- Matière : cellulose + résine agréée FDA
- Ruban bleu

APPLICATIONS

- Utilisé pour les précipités volumineux
- Fer, cobalt et chrome
- Hydroxyde de cuivre, bismuth
- Cobalt et sulfure de fer

SPECIFICATIONS TECHNIQUES

CARACTERISTIQUES	VALEURS	UNITE	NORMES
Poids	84	g/m²	DIN 53104
Epaisseur	0.17	mm	
Porosité	2-4	µm	
Vitesse de filtration	195	sec.	DIN 53137
Résistance à l'éclatement	0.3	kg/cm²	
Taux de cendres	<0.01	%	DIN 53138

DONNEES COMMERCIALES

Disponibles en :

- Feuilles : F
- Disques à plat : A
- Disques plissés : P

DOMINIQUE DUTSCHER SAS

TECHNICAL DATA

GRADE QT55

DESCRIPTION

- Very slow quantitative filter paper (without ash)
- Material: cellulose + FDA approved resin

APPLICATIONS

- Used for voluminous precipitates
- Iron, cobalt and chromium
- Hydroxide copper, bismuth
- Cobalt and iron sulphide

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	VALUES	UNITS	STANDARDS
Weight	84	g/m²	DIN 53104
Thickness	0.17	mm	
Pore size	2-4	µm	
Filtration speed	195	sec.	DIN 53137
Burst strength	0.3	kg/cm²	
Ash rate	<0.01	%	DIN 53138

SALES INFORMATION

Available in:

- Sheets: F
- Plain discs: A
- Folded discs: P

DOMINIQUE DUTSCHER SAS