FICHE TECHNIQUE

GRADE FT307

DESIGNATION

- Plaque filtrante
- Matière : cellulose, kieselguhr
- Liant : agent polyamide approuvé FDA

APPLICATIONS

- Procédés industriels : cosmétique, pharmaceutique, agro-alimentaires, chimie…
- Clarification
- Filtration dégrossissante de la cire, vins blancs, rouges et rosés, apéritifs, vins pétillants
- Filtration clarifiante des produits photo-réactifs, liquides visqueux, huiles d'olive, sirops de sucre, jus de raisin, spiritueux

SPECIFICATIONS TECHNIQUES

CARACTERISTIQUES	VALEURS	UNITES
Grammage	1100	g/m²
Epaisseur	3.35	mm
Porosité	2.0-7.0	µm
Porosité max.	24.5	µm
Perméabilité	450	L/m²/mm

DONNEES COMMERCIALES

- Disponibles avec ou sans trous en disques à plat (A) ou en feuilles (F) ou en modules lenticulaires

DOMINIQUE DUTSCHER SAS

TECHNICAL DATA

GRADE FT307

DESCRIPTION

- Filter sheets
- Material: cellulose, kieselguhr
- Binder: FDA approved polyamide agent

APPLICATIONS

- Industrial applications: cosmetics, pharmaceuticals, foods, chemicals…
- Clarification
- Coarse filtration of wax, white, red and rosé wines, aperitifs, sparkling wines
- Clarifying filtration of photo-reactive products, viscous liquids, olive oils, sugar syrups, grape juice, spirits

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	VALUES	UNITS
Weight	1100	g/m^2
Thickness	3.35	mm
Pore size	2.0-7.0	µm
Max. pore size	24.5	µm
Permeability	450	$L/m^2/mm$

SALES DATA

- Available with or without holes in plain discs (A) or in sheets (F) or in lenticular modules

DOMINIQUE DUTSCHER SAS