FICHE TECHNIQUE

GRADE ST60

DESIGNATION

- Papier filtre standard
- Matière : 100% cellulose
- Liant : résine agréée FDA

APPLICATIONS

- Papier pour tous travaux de laboratoire (écoles, lycées)
- Protection de paillasse
- Sulfure d'étain et de potasse
- Lessive de soude
- Hydroxyde de cobalt et de cadmium…

SPECIFICATIONS TECHNIQUES

CARACTERISTIQUES	VALEURS	UNITE	NORMES
Poids	64	g/m²	DIN 53104
Epaisseur	0.15	mm	
Porosité	10-20	µm	
Vitesse de filtration	50	sec.	DIN 53137
Résistance à l'éclatement	1.45	kg/cm²	
Taux de cendres	0.1	%	DIN 53138

DONNEES COMMERCIALES

Disponibles en :

- Feuilles : F
- Disques à plat : A
- Disques plissés : P

DOMINIQUE DUTSCHER SAS

TECHNICAL DATA

GRADE ST60

DESCRIPTION

- Standard filter paper
- Material: 100% cellulose
- Binder: FDA approved resin

APPLICATIONS

- Paper for all laboratory work (schools, high schools)
- Bench-top protection
- Tin and potash sulphide
- Sodium hydroxide solution
- Cobalt and cadmium hydroxide…

TECHNICAL SPECIFICATIONS

CHARACTERISTICS	VALUES	UNITS	STANDARDS
Weight	64	g/m²	DIN 53104
Thickness	0.15	mm	
Pore size	10-20	µm	
Filtration speed	50	sec.	DIN 53137
Bursting strength	1.45	kg/cm²	
Ash rate	0.1	%	DIN 53138

COMMERCIAL DATA

Available in:

- Sheets: F
- Plain discs: A
- Folded discs: P

DOMINIQUE DUTSCHER SAS