Medicom

SafeMask® Fit+Pro

Technical Data Sheet

M63110V FFP3 NR respiratory protective mask – with valve

Category III Personal Protective Equipment

DOMINIQUE DUTSCHER SAS



FEATURES & BENEFITS

- Folded 3-panel design adapts to various face shapes and sizes.
- Sealing foams on both the upper and lower panels ensure a perfect seal while providing unmatched comfort for the wearer.
- Easy to put on and adjust thanks to sliding elastic straps and a tightening ring.
- The exhalation valve effectively expels heat and humidity, reducing the risk of fogging on the wearer's glasses.
- Its individual packaging helps control the risk of contamination.

Recommended uses

- Protection against toxic aerosols and high level of fine dust (asbestos)
- Environments with high concentrations of pollutants
- Work in hazardous industrial environments (chemistry, welding, grinding)
- Hospitals and high-security laboratories (handling highly contagious pathogens)
- Work in areas with a risk of exposure to highly transmissible diseases especially during pandemic

PRODUCT DETAILS

Product name :	**SafeMask® Fit+Pro**
Product type :	Single use, non sterile
Fasteners:	Sliding transverse elastics
Composition :	Nose strip: Aluminum Foams: PVC Valve: Polypropylene + silicone Elastics: Spandex + polyester Inner & outer layers: Spunbond polypropylene Filter: Meltblown polypropylene
Origin :	China

Item	FFP Class	Valve Yes/no	Elastic Color	Unit weight (+/- 10%)	Qty / box
M63110V	FFP3 NR	Yes	Red	19 g	12

M63110V FFP3 NR respiratory protective mask – with valve

Category III Personal Protective Equipment

CERTIFICATIONS & STANDARDS

- In accordance with requirements of Reg (EU) 2016/425 on personal protective equipment.
- Comply with the applicable standard EN 149:2001+A1:2009.

EN 149:2001+A1:2009				
TEST	FFP3 REQUIRED LEVEL	LABORATORY	REPORT N° & DATE	RESULTS
Oil paraffin penetration	< 1 % after 120mg exposure	Inspec International BV (2849)	No 1.24.11.21 12/11/2024	Compliant
NaCl penetration	< 1 % after 120mg exposure			
Total inward leakage	≤ 5 % for at least 46 results over 50 ≤ 2 % for at least 8 arithmetic average over 10			
Air permeability inhalation 30 l/min	≤ 1 mbar			
Air permeability inhalation 95 l/min	≤ 3 mbar			
Air permeability exhalation 160 l/min	≤ 3 mbar			
Carbon dioxide content	< 1,0 %			
Flammability	Must not burn or continue to burn for more than 5 seconds after the withdrawal of the flame			
Annual surveillance according to module D - Reg (EU) 2016/425 done by BSI (2797)				

LOGISTICS

Item	FFP Class	Mask qty per box	Box size	Poids boîte	Boxes qty per case	Case size	Poids carton
M63110V	3	12	245 x 95 x 240 mm	350 g	12	508 x 305 x 498 mm	4,65 kg

EAN Codes

Article	Carton	Boîte
M63110V	3 662 036 023 797	3 662 036 023 803

DOMINIQUE DUTSCHER SAS

Medicom

Medicom SAS
Bld de la chanterie | 49124 Saint Barthélemy d'Anjou – France
T : 33 (0) 241 963 434 | F : + 33 (0) 241 963 453 | sales.support.pro.eu@medicom.com | www.medicom-eu.com