Medicom
Kolmi®
Feeldry

Technical Data Sheet

M24101-40 Medical mask with ties-on - Type II - Kolmi® Feeldry

Medical Device Class I

DOMINIQUE DUTSCHER SAS

FEATURES & BENEFITS



- Protects the environment from droplets emitted by the wearer
- Effective against bacteria, particles and viruses (BFE, PFE, & VFE)
- Kolmi® masks feature the exclusive Origami folding for greater comfort and a perfect fit on the wearer's face.
- Featuring a wide and ultra-flexible nose strip, they ensure an excellent fit to the face and effectively limit leakage around the nose, thereby significantly reducing fogging.
- For maximum comfort, the inner layer is designed with a material that limits irritation to the face.
- With Feeldry technology the inner layer has been specially designed to absorb perspiration and avoid the feeling of humidity inside the mask.
- Hypoallergenic.

RECOMMENDED USE

- For use by medical staff
- Medical masks can also be worn by patients and others to reduce the risk of spreading infection, particularly in epidemic or pandemic situations.

PRODUCT DETAILS

Product name :	Kolmi® Feeldry Type II
Product type :	Single use, non sterile
Fasteners :	Ties-on
Nose piece :	Polypropylene and steel
Size :	95 x 175 mm
Unit weight :	3,5 g
Quantity / box :	60 masks
Origin :	France

Item	Color
M24101-40	Blue

CERTIFICATIONS & STANDARDS

Meet the requirements of Regulation (EU) 2017/745 on medical devices.
Meets applicable requirements of EN 14683:2025*.
Manufacturing site: ISO 9001 and ISO 13485 certification.

MICROBIOLOGICAL INFORMATION

Assessment of initial microbial contamination according to standards EN 14683:2025* & ISO 11737: 2018+A1:2021.
Additional microbiological controls: ASR, E.coli, Staphylococci, available upon request.

M24101-40 Medical mask with ties-on - Type II - Kolmi® Feeldry

Medical Device Class I

EN 14683:2025*					
TEST	STANDARD	REQUIRED LEVEL	LABORATORY	REPORT N° & DATE	AVERAGE RESULTS
Bacterial Filtration Efficiency : BFE	EN 14683:2025*	≥ 98% (Type II)	Centexbel	22.00553.01 09/02/2022	98,7 %
DELTA P	EN 14683:2025*	≤ 200 Pa	Centexbel		108,3 Pa
Particles Filtration Efficiency 0,1 µm : PFE	ASTM F2299	No requirements	Nelson	1393992-S01 12/03/2021	99,6 %
Viral Filtration Efficiency : VFE	ASTM F2101	No requirements	Nelson	1362439-S01 22/12/2020	98,7 %

* based on testing to EN14683:2019 + AC:2019

PRECAUTIONS

The mask must be used on intact skin only.
The reuse or extended use may lead to infection or cross-contamination.
Please refer to your national legislation on the subject of disposal of this product once it has been used.

STORAGE CONDITIONS

Normal conditions of conversation & storage: not to be exposed to moisture and sunlight, must be stored at room temperature.
Shelf life of the product: 5 years.

PACKAGING MARKING

CE MD Medical Device LATEX *

* Do not use if package is damaged

LOGISTICS

Outer case spec.

Item	Size (mm)	Gross weight (kg)	QTY/ pallet
M24101-40	400 x 400 x 178	1,9	54

Inner box spec.

Size (mm)	Gross weight (g)	Packaging
192 x 125 x 165	265	6 boxes x 60 masks

EAN Codes

Item	Outer case	Inner Box
M24101-40	3 701 407 400 338	3 701 407 400 321

DOMINIQUE DUTSCHER SAS

Medicom

Medicom SAS
Bld de la chanterie | 49124 Saint Barthélemy d'Anjou – France
T : 33 (0) 241 963 434 | F : + 33 (0) 241 963 453 | sales.support.pro.eu@medicom.com | www.medicom-eu.com