Standard Solution for the NanoPhotometer® NP80/N60/N50

The Standard Solution is available in two packages: **N-568-S2** including two vails and **N-568-S** including ten vails

The Standard Solution is used to verify the absorbance accuracy of the NanoPhotometer[®] NP80/N60/N50 NanoVolume options. It is included in the IQ/OQ documentation for the NanoPhotometer[®] NP80 (N-80-Q) and N60 (N-60-Q).

Hazardous information: Please read the Material Safety Data Sheet carefully prior to using this product.

All required information about the Standard Solution is available on the Standard Solution box label:

Example label:

Standard Solution for the NanoPhotometer NP80/N60/N50

 Potassium hydrogen phthalate
 (PHP)

 Item No:
 N-568-S2

 CAS-No:
 877-24-7

 Lot No:
 1702

 10 mm Absorbance (280nm):
 21.73 A

 @ 20 - 25°C
 Expiration date:
 see label

 Implen GmbH, Schatzbogen 52, D-\$1829 München, Germany

Note: Specifications for the Standard Solution are guaranteed for one year. Please refer to expiration date on the box. Once a vail is opened, the Standard Solution can be used for 30 minutes. For most accurate results, the NanoPhotometer® should be turned on 15 minutes prior to taking the readings.

Check of Absorbance Accuracy:

- 1. Open Method: More Apps => Wavelength
- 2. Set the following parameter: Dilution 15 (NP80/N60) and Dilution 140 (N50); Wavelength 280 nm; Baseline Correction 377nm; Smoothing 1
- 3. Clean measurement head (sample window and mirror) with 70% Ethanol and subsequently with clean water
- 4. Blank with 1.5 µl water
- Clean measurement head (sample window and mirror) with lint free tissue
- 6. Before opening a vial, mix it vigorously and make sure that the whole liquid collects at the bottom of the vial. Break the vial carefully at the predetermined breaking point (white line).

Caution: Danger of injury at the breaking edge!

- 7. Apply 1.5 µl Standard Solution. Close the sample arm immediately and measure. Result should be within +/- 5% (dilution 15) and +/- 10% (dilution 140) of the certified absorbance value.
- 8. Clean measurement head (sample window and mirror) with 70% Ethanol and subsequently with clean water

Note: To achieve best and certified absorbance values all readings must be taken within a temperature range of 20°C – 25°C.

Ordering Information:

Item Number:	Description:
N-568-S	Standard Solution (10 x 0.5 ml) for the control of the photometric accuracy of the
	NanoPhotometer® NP80, N60 and N50 (NanoVolume)
N-568-S2	Standard Solution (2 x 0.5 ml) for the control of the photometric accuracy of the
	NanoPhotometer® NP80, N60 and N50 (NanoVolume)

For questions please contact the Implen Support Team: support@implen.de / +49-89-7263718-20



telephone: +49-89-7263718 0 fax: +49-89-7263718 54 email: support@implen.de www.implen.de

