HANNA instruments


EN

instruments	HI93749-0 -	- Chrom	ium VI LR F	Reagent	Page n. 1 / 11 Replaced revision:3 (Dated 21/01/2023)
		Sof	oty Data SI	aaat	
		Sal	ety Data Sl	leel	
	According to Annex	II to REACH	- Regulation 2020/87	'8 and to Annex II to	D UK REACH
ECTION 1. Identific	cation of the substa	ince/mixtu	re and of the co	ompany/under	taking
1. Product identifier					
Code		HI93749-0			
Product name		Chromium '	VI LR Reagent		
2. Relevant identified uses	s of the substance or mixtu	ire and uses a	advised against		
Intended use		Determinati	ion of Chromium(VI)	in Water Samples.	
3. Details of the supplier o	f the safety data sheet				
Name			ruments S.R.L.		
Full address District and Country		str. Hanna I 457260	Nr 1 loc. Nusfalau		(Salai)
District and Country		407200	Romania		(Salaj)
		Tel. Fax	+40 260607700 +40 260607700		
e-mail address of the corresponsible for the Safety		msds@han			
4. Emergency telephone n	number				
For urgent inquiries refer	to	Internationa hours/365 c		JK, London: +44 20	038073798 - CHEMTREC 24
SECTION 2. Hazards identi	fication				
2.1. Classification of the sub	ostance or mixture				
amendments and supple 2020/878.	as hazardous pursuant to ments). The product thus i n concerning the risks for l	requires a saf	ety datasheet that co	mplies with the pro	visions of (EU) Regulation
Hazard classification and	I indication:				
Acute toxicity, categor	ry 3		H331	Toxic if inhaled.	
Skin corrosion, catego			H314		skin burns and eye damage.
Serious eye damage, Hazardous to the agu	category 1 atic environment, chronic		H318 H412	Causes serious	eye damage. atic life with long lasting effects.
toxicity, category 3			11712	nannur to aqua	אוס וויס שונו וסווץ ומסנוויץ בוובטנס.
2. Label elements					
Hazard labelling pursuan	t to EC Regulation 1272/2	008 (CLP) an	d subsequent amend	Iments and suppler	ments.
Hazard pictograms:					
Signal words:	Danger				
Hazard statements: H331	Toxic if inhold				
	Toxic if inhaled.				

Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects. Corrosive to the respiratory tract.

Precautionary statements:

H314 H412 EUH071



SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

POTASSIUM DISULFATE Irritation and corrosion, Cough, Shortness of breath. Risk of blindness!.

SULPHAMIC ACID Irritant effects, Cough, Shortness of breath, Pain, shock.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available



Hanna Instruments S.R.L. HI93749-0 - Chromium VI LR Reagent

ΕN

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

POTASSIUM DISULFATE

Not combustible. Ambient fire may liberate hazardous vapours. Fire may cause evolution of: Sulphur oxides.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust. Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):



Hanna Instruments S.R.L. HI93749-0 - Chromium VI LR Reagent

Revision nr.4 Dated 19/03/2023 Printed on 19/03/2023 Page n. 4/11 Replaced revision:3 (Dated 21/01/2023)

SECTION 7. Handling and storage ... / >>

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

			DOTAGE	JM DISULFATE				
Predicted no-effect conc	ontration D	NEC	PUTASSI					
Normal value in fresh						0,68	mg/l	
Normal value in marin						0.068	mg/l	
Normal value for fres		mont				2,5	mg/kg/d	
Normal value for mar						0.25	mg/kg/d	
Normal value for wate						6,8	mg/l	
Normal value of STP	,					800	mg/l	
Normal value for the f	•					0.092	mg/kg/d	
Health - Derived no-effect						0,092	mg/kg/u	
lealth - Denveu no-enet		n consumers			Effects on w	orkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
Route of exposure	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation	local	Systemic	local	Systemic	local	Systemic	0.13	0,13
Innalation							mg/m3	mg/m3
Normal value in fresh	water					1,8	mg/l	
Normal value in marir	ne water					0,18	mg/l	
Normal value for fresl	h water sedi	ment				8,36	mg/kg/d	
Normal value for mar	ine water se	diment				0,84	mg/kg/d	
Normal value for wate	er, intermitte	nt release				0,48	mg/l	
Normal value of STP	microorgani	sms				20	mg/l	
Normal value for the	terrestrial co	mpartment				5	mg/kg/d	
Health - Derived no-effect	ct level - DN	EL / DMEL						
	Effects or	n consumers			Effects on w	orkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral			VND	5 mg/kg bw/d				
Inhalation			VND	17,4			VND	70,5
				mg/m3				mg/m3
Skin			VND	5			VND	10
				mg/kg bw/d				mg/kg

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374). Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

bw/d



Decomposes at 205°C/401°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

SULPHAMIC ACID

Risk of explosion on contact with chlorine. Reacts dangerously with metal nitrites and nitrates.

EPY 11.3.0 - SDS 1004.14



HI93749-0 - Chromium VI LR Reagent

SECTION 10. Stability and reactivity ... / >>

Avoid environmental dust build-up.

POTASSIUM DISULFATE Exposure to moisture.

10.5. Incompatible materials

SULPHAMIC ACID Chlorine, nitric acid, sodium nitrites and nitrates, potassium.

10.6. Hazardous decomposition products

SULPHAMIC ACID

Sulphur oxides and nitric oxides.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

POTASSIUM DISULFATE

Acute inhalation toxicity, absorption, Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages, damage of respiratory tract, Lung oedema, Symptoms may be delayed - Skin irritation (in analogy to similar products), Causes severe burns. - Eye irritation (in analogy to similar products), Causes serious eye damage. Risk of blindness!

SULPHAMIC ACID

Acute oral toxicity, Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract., Pain, Possible damages:, shock - Acute inhalation toxicity, Symptoms: Cough, Shortness of breath, Irritation symptoms in the respiratory tract - Skin irritation, Result: Irritations, Causes skin irritation - Eye irritation, rabbit, Result: Severe irritations, Causes serious eye irritation.

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:

Corrosive to the respiratory tract.

POTASSIUM DISULFATE LD50 (Oral): LC50 (Inhalation mists/powders):

SULPHAMIC ACID LD50 (Dermal): LD50 (Oral): > 2000 mg/kg Rat

2140 mg/kg Rat

0,85 mg/l/4h Rat

Not classified (no significant component)

Not classified (no significant component)

1.5 ma/l

1050 mg/kg Guinea pig

SKIN CORROSION / IRRITATION

Corrosive for the skin Classification according to the experimental Ph value

SERIOUS EYE DAMAGE / IRRITATION

EN



Hanna Instruments S.R.L. HI93749-0 - Chromium VI LR Reagent

Revision nr.4 Dated 19/03/2023 Printed on 19/03/2023 Page n. 7 / 11 Replaced revision:3 (Dated 21/01/2023)

Instruments	HI93749-0 - C	Information of LK Reagent					
SECTION 11. Toxicologica	l information / >>						
Causes serious eye damag	е						
RESPIRATORY OR SKIN SENSITISATION							
Does not meet the classification criteria for this hazard class							
GERM CELL MUTAGENICITY							
Does not meet the classifica	Does not meet the classification criteria for this hazard class						
CARCINOGENICITY							
Does not meet the classifica	Does not meet the classification criteria for this hazard class						
REPRODUCTIVE TOXICIT	Y						
Does not meet the classifica	ation criteria for this hazard cl	lass					
STOT - SINGLE EXPOSUR	<u>E</u>						
Does not meet the classification	ation criteria for this hazard cl	lass					
STOT - REPEATED EXPOS	SURE						
Does not meet the classifica	ation criteria for this hazard cl	lass					
ASPIRATION HAZARD							
Does not meet the classifica	ation criteria for this hazard cl	lass					
11.2. Information on other haze	ards						
Based on the available data disruptors with human healt		n substances listed in the main European lists of	potential or suspected endocrine				
SECTION 12. Ecologi	cal information						
This product is dangerous for	or the environment and the a	quatic organisms. In the long term, it have negati	ve effects on aquatic environment.				
12.1. Toxicity							
POTASSIUM DISULFATE							
LC50 - for Fish EC50 - for Crustacea		680 mg/l/96h Pimephales promelas 720 mg/l/48h Daphnia magna					
SULPHAMIC ACID							
LC50 - for Fish		70,3 mg/l/96h Pimephales promelas					
12.2. Persistence and degrada	ıbility						
SULPHAMIC ACID							
Solubility in water Degradability: information n	ot available	> 10000 mg/l					
12.3. Bioaccumulative potentia	ıl						
SULPHAMIC ACID Partition coefficient: n-octan	ol/water	0,1 Log Kow					
12.4. Mobility in soil							
Information not available							
12.5. Results of PBT and vPvE	3 assessment						
		ain any PBT or vPvB in percentage ≥ than 0,1%.					
	, ,	,					
			@EPY 11.3.0 - SDS 1004.14				

EN



HI93749-0 - Chromium VI LR Reagent

SECTION 12. Ecological information ... / >>

12.6. Endocrine disrupting properties

SULPHAMIC ACID

Biological effects: Harmful effect due to pH shift. Further information on ecology, Discharge into the environment must be avoided.

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 2923

14.2. UN proper shipping name

ADR / RID:	CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE) MIXTURE
IMDG:	CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE) MIXTURE
IATA:	CORROSIVE SOLID, TOXIC, N.O.S. (POTASSIUM DISULFATE) MIXTURE

14.3. Transport hazard class(es)

ADR / RID:	Class: 8	Label: 8 (6.1)	
IMDG:	Class: 8	Label: 8 (6.1)	
IATA:	Class: 8	Label: 8 (6.1)	

Ш

14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:

IMDG: IATA: HIN - Kemler: 86 Special provision: -EMS: F-A, S-B Cargo: Pass.: Special provision: Limited Quantities: 1 kg

Limited Quantities: 1 kg Maximum quantity: 50 Kg Maximum quantity: 15 Kg A3, A803 Tunnel restriction code: (E)

Packaging instructions: 863 Packaging instructions: 859 EN

19/03/2023 on 19/03/2023 8 / 11 id revit

on:3 (Dated 21/01/2023)

HANNA	Hanna Instruments S.R.L.	Revision nr.4 EN Dated 19/03/2023 Printed on 19/03/2023				
instruments	HI93749-0 - Chromium VI LR Reagent	Page n. 9 / 11 Replaced revision:3 (Dated 21/01/2023)				
SECTION 14. Transport information / >>						
14.7. Maritime transport in bulk according to IMO instruments						
Information not relevant						
SECTION 15. Regulat	ory information					
-	nmental regulations/legislation specific for the substance or mixture					
Seveso Category - Directive	2012/18/EU: H2					
Restrictions relating to the p Contained substance	product or contained substances pursuant to Annex XVII to EC Regulation 19	907/2006				
	75					
Regulation (EU) 2019/1148	- on the marketing and use of explosives precursors					
not applicable						
Substances in Candidate Lize On the basis of available date	st (Art. 59 REACH)					
Substances subject to authon None	Substances subject to authorisation (Annex XIV REACH)					
Substances subject to expo	rtation reporting pursuant to Regulation (EU) 649/2012:					
None						
Substances subject to the R None	Rotterdam Convention:					
Substances subject to the S	Stockholm Convention:					
None						
Healthcare controls						
	emical agent must not undergo health checks, provided that available risk-ass h and safety are modest and that the 98/24/EC directive is respected.	sessment data prove that the fisks				
	German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)					
WGK 1: Low hazard to waters						
15.2. Chemical safety assessment						
A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.						
SECTION 16. Other in	formation					
Text of hazard (H) indication	ns mentioned in section 2-3 of the sheet:					
Acute Tox. 3	Acute toxicity, category 3					
Skin Corr. 1A Eye Dam. 1	Skin corrosion, category 1A Serious eye damage, category 1					
Eye Irrit. 2	Eye irritation, category 2					
Skin Irrit. 2 Skin irritation, category 2						
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3					
H331 H314	H331 Toxic if inhaled. H314 Causes severe skin burns and eve damage.					

Causes severe skin burns and eye damage. Causes serious eye damage. H318 H319 Causes serious eye irritation. H315 Causes skin irritation. Harmful to aquatic life with long lasting effects. Corrosive to the respiratory tract. H412 EUH071

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
 CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008



HI93749-0 - Chromium VI LR Reagent

SECTION 16. Other information ... / >>

ΕN

nsion nr.4 ed 19/03/2023 ted on 19/03/2023 je n. 10 / 11 placed revision:3 (Dated 21/01/2023)

- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for



HI93749-0 - Chromium VI LR Reagent

EN

SECTION 16. Other information ... / >>

evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 01 / 03.