

APW-200 Microplate Washer

Microplate washer is an automatic plate washer for washing 96-well microplate, compact construction, efficient washing and durable. It is suitable for the washing of flat bottom, U-shaped bottom, v-shaped bottom, c-shaped bottom of various specifications. It has various special functions selected and matched by other board washer. The programmed design is especially suitable for laboratory with heavy workload of multi-application of microplate. It can also be used to soak and shock.



Features

1. Low residual liquid, each well ≤ 1μL
2. 4.3 inch color LCD display, easy to operate .
3. Microplate can be soaked and shocked simultaneously
4. Strainer in the pipeline and automatic washing functions avoid the liquid blocking the pipeline
5. Pipeline flushing and distilled water washing functions can be set, flushing time and number of spacers can be adjusted.
6. With pause function, you can continue to complete the rest of washing procedures.
7. Washing bottle has uniform volume calibration line, alarm function to avoid the washing liquid used up or waste liquid from overflow.
8. 100 programs can be save.

Specification

Residual liquid	≤1μL
Washing heads	1×8 or 1×12 heads
Plate types	Flat, U, V, C bottom
Washing method	Sling-point, two-point and multi-point
Washing volume	50-2000μL, increase by 50μL
Washing times	1-99 times
Washing channels	3
Bottles	3pcs 2.5L washing bottle, 1pc 2.5L washing bottle
Dispense accuracy	≤2%@300μL
Liquid injection accuracy	CV≤1.5%@300μL
Soaking and shaking time	99'0"
Date connection	USB
Weight	12kg
Power supply	AC110/240V; 50/60Hz

APW-200 Highlights

Easy Operation

The APW-200 Microplate Washer has 4.3 inch LCD display with friendly interface. U-disk can be used to transfer the data between the PC and the washer. Or between two washers, it can also be used to upgrade the software. The washing head can be replaced easily for different kinds of microplates.

Safety and reliable feature

The APW-200 Microplate Washer is equipped with liquid position sensor to avoid the washing liquid used up or waste liquid from overflow, minimize the risk and avoid the liquid being sucked into the pump to break the equipment. Besides it has shaking function, which can improve the washing efficiency.

AMR-100 Microplate Reader

Code	Description	Code	Description
AS-16050-00	AMR-100 Microplate Reader	AS-16051-17	Optical filter 510nm
AS-16051-01	Optical filter 340nm	AS-16051-18	Optical filter 520nm
AS-16051-02	Optical filter 380nm	AS-16051-19	Optical filter 532nm
AS-16051-03	Optical filter 405nm	AS-16051-20	Optical filter 546nm
AS-16051-04	Optical filter 415nm	AS-16051-21	Optical filter 560nm
AS-16051-05	Optical filter 450nm	AS-16051-22	Optical filter 562nm
AS-16051-06	Optical filter 492nm	AS-16051-23	Optical filter 600nm
AS-16051-07	Optical filter 540nm	AS-16051-24	Optical filter 620nm
AS-16051-08	Optical filter 570nm	AS-16051-25	Optical filter 646nm
AS-16051-09	Optical filter 578nm	AS-16051-26	Optical filter 663nm
AS-16051-10	Optical filter 590nm	AS-16051-27	Optical filter 700nm
AS-16051-11	Optical filter 595nm	AS-16051-28	Optical filter 750nm
AS-16051-12	Optical filter 630nm	AS-16051-50	Replacement Lamp
AS-16051-13	Optical filter 650nm	AS-16051-51	Printer
AS-16051-14	Optical filter 690nm	AS-16051-52	Printer paper
AS-16051-15	Optical filter 470nm	AS-16051-53	Calibration Plate
AS-16051-16	Optical filter 490nm	AS-16051-54	ReaderIt software


FlexA-200 Microplate Reader

Code	Description
AS-19010-00	FlexA-200 Microplate Reader
AS-19011-01	ReaderIt software
AS-16051-26	Printer
AS-16051-27	Printer Paper

APW-200 Microplate Washer

Code	Description
AS-16020-00	APW-200 Microplate Washer 110V-240V, 50/60Hz
AS-16011-01	8 needles washing head
AS-16011-02	12 needles washing head
AS-16011-03	Washing bottle
AS-16011-04	Waste liquid bottle

All for life science



AMR-100
Microplate Reader

FlexA-200
Microplate Reader

APW-200
Microplate Washer

FlexA-200 Microplate Reader

FlexA-200 full-wavelength Microplate reader is a high-quality Microplate reader based on grating monochromator with a wavelength range of 200-1000 nm. It can be used for spectroscopic scanning, endpoint method and kinetic detection. It is suitable for 96 well plates and 384 well plates with or without cover. FlexA-200 can be shocked and cultured by micro porous plate, and the highest temperature of culture is up to 45 °C.

FlexA-200 Microplate reader can be operated independently by the built-in software of the instrument, and can be controlled by PC using ReaderIt-II software.



■ Specification

Display	10 inch touch screen
Light source	Quartz-halogen lamp
Wavelength range	200 - 1000 nm with 1nm
Wavelength accuracy	±2 nm
Wavelength repeatability	±0.2 nm
Wavelength selection	Monochromator
Reader-out range	0 - 4.0 OD
Half-bandwidth of filters	<2.5 nm
Detector	Two silicon photoelectric detector, one for measurement, another for reference
Linearity @450nm	0 - 2.5 Abs, ±2% (96 well plates)
Accuracy @450nm	1.0% ± 0.005 Abs (0 - 2.0 Abs); 2.0% (2.0 - 2.5 Abs)
Precision @450nm	CV < 0.5% accuracy model; CV < 1.0% fast model
Test speed	10 seconds with 96-well plate (fast mode); 30seconds with 96-well plate (accurate mode)
Plate shaking	Linear, three options for speed
Test speed	15 seconds with 96-well plate (single wavelength); 30seconds with 96-well plate(double wavelength)
Incubator	From ambient +5°C
UI	Integrated software or PC control software
Analysis software	ReaderIt-II
User interface	Touch screen, android system, 10 inch touch screen, external keyboard mouse
Storage	16G memory, more than 10000 test records can be stored
Ports	3 USB ports, for PC, USB-disk, printer
Automated systems	Temporarily uncompatible with automated systems
Power supply	DC24V 6.5A
Dimension(W*D*H)	300×500×290mm
Weight	15kg

Choose detection wavelength freely with raster

FlexA-200 adopt the xenon flash lamp as light source, which chooses the wavelength range from 200-1000nm with 1nm step by grating monochromator for the full spectrum scanning only needs 15 seconds each sample.

Friendly operation interface which can complete fast detection in FlexA-200

The built-in software of Flex-200 which has 10 inch high resolution touch screen and adopts the graphic interface, it makes the operations easy. In addition, you can use USB to export data.



ReaderIt-II software has the strong data analysis and advanced detection setting ability

Graphic interface ReaderIt-II realized the simulation demonstration function. The data analysis function includes quantitative curve fitting, quantitative analysis, kinetics calculation, custom equation and 4 parameter fitting and so on. Data can be exported to Excel format easily, and the detailed report also can be exported by the built-in tools.

FlexA-200 instrument built-in software and ReaderIt-II software are both Chinese/English interface intuitive graphical interface is convenient for customers to use.



High quality data and stabilized performance

The optical system makes sure the high quality data and stabilized performance of FlexA-200.

- Double beam optical system has the reference optical channel system, which make the data more stabilization.
- Self checking system make sure the device running stabilized.
- Long life xenon lamp which can be used for 10⁵ times.

Incubator function

Temperature range: ambient +5°C to 45°C.
Average temperature difference: ±0.5°C (at 37°C).
Uniformity: <1.0°C (96 well plate without cover, at 37°C).

Liner shaking function for microplate

Three options for the shaking speed: Low speed, Intermediate speed and High speed.
Low speed: 5Hz, amplitude 15mm.
Intermediate speed: 11Hz, amplitude 3mm.
High speed: 20Hz, amplitude 1mm.

Wide and convenient application

FlexA-200 can be used for spectrum scanning, end point and kinetic detection in 96/384-well plates.

Applications:

- DNA/RNA quantitative and purity analysis.
- Protein quantitative.
- Enzymology and immune detection.
- Kinetic detection.
- Cell multiplication and cytotoxicity detection.

Easy to use:

- Raster full wavelength which can be used for spectrum scanning to find the best detection wavelength.
- Small bandwidth (< 2 nm) and higher wavelength accuracy.
- Touch screen and built-in graphic interface software with android system make the operation easy.
- Friendly used of ReaderIt-PC software.
- With the function of incubation oscillation, Heating lid incubation reduces liquid evaporation.
- Software upgrade for free.

Energy saving mode

- Stepper motor and incubator shut down.
- Display turns darken.
- Click any button to quit the energy saving mode.

AMR-100 Microplate Reader

AMR-100 Microplate reader is a high-quality optical absorption microplate reader based on filters. Its wavelength range is 340-750 nm. It is suitable for scientific research and clinical application. It is suitable for 96 well plates and can meet the requirements of different channel.

■ Features

- Easy use with 7 inch touch screen together with 3 external keys.
- Able to use individually or connect with PC and controlled by an android tablet and the results can be putout.
- Absorbance range: 0.0-4.00Abs, meeting different needs.
- 8 positions optical filter wheel, equipped with 4 standard filters, other filters are optional.
- Built-in software can provide control program and date analysis, can connect with U-disk.
- Fast and accurate measurement of 96-well plates within 6 seconds.

AMR-100



■ Specification

Display	7 inch touch screen (800x480 dots)
Light source	Quartz-halogen lamp 6V/10W
Wavelength	340nm~750nm
Half-bandwidth of filters	8-10 nm
Optical filters	8 positions optical filter wheel, equipped with 4 standard optical filters, 450nm, 492nm, 630nm other filters are optional
Read-out range	0-4.00Abs
Linearity (405nm)	0-3.0Abs, ±1%; 3-4.0Abs, ±2%
Resolution	0.001Abs
Accuracy (405nm)	±1% (0-3Abs); ±2% (3-4Abs)
Precision(405nm)	CV<0.2% (0-3Abs); CV<1% (3-4Abs)
Test speed	6s, 96-wells plates, fast measurement mode; Single wavelength <15s/96well , dual wavelength <28s/96well
Sensitivity / Detector	20.010 / Photodiode
User interface	Integrated software or PC control software
Storage	200 programs and 100,000 test records
Ports	3USB ports, for PC, printer and USB-disk
Power supply	AC 100-240V, 50-60Hz, 2A
Dimensions(W*D*H)	440×295×225mm
Weight(kg)	10kg

■ AMR-100 Highlights

- Easy of use with 7 inch touch screen , simple and intuitive operation. No need to operate keyboard.
- It keeps with high visual, convenient and practical.
- It is equipped with standard control and data analysis software ReaderIt-, data detection, convenient and fast; powerful data analysis function and excellent results report not only can run independently, but also can run analysis on computer and Pad.
- Convenience replace light source and filter without opening the shell.

