

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Securline Lab Marker - Red
Registration number	-
Synonyms	None.
SDS number	014
Issue date	15-February-2017
Version number	01
Revision date	-
Supersedes date	-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Lab Marking Ink
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company name	Aspen Medical Europe Ltd.
Address	Clinitron House, Ashby Park, Ashby-de-la-Zouch, Leicestershire, LE65 1JG
Telephone	01530 411000 0800 032 3399
E-mail	customers@aspenmedicaleurope.com
1.4. Emergency telephone number	+44 (0)1530 562216

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
-------------------	------------	-------------------------------------

Health hazards

Acute toxicity, dermal	Category 4	H312 - Harmful in contact with skin.
Acute toxicity, inhalation	Category 4	H332 - Harmful if inhaled.
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Reproductive toxicity	Category 2	H361 - Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation	H335 - May cause respiratory irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Category 2 (Central nervous system, Hearing organs, Kidney, Liver)	H373 - May cause damage to organs (Central nervous system, Hearing organs, Kidney, Liver) through prolonged or repeated exposure.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

Hazard summary

May be ignited by heat, sparks or flames. May be fatal if swallowed and enters airways. Harmful if inhaled. Harmful in contact with skin. May cause damage to organs through prolonged or repeated exposure. Causes serious eye irritation. Causes skin irritation. May cause irritation to the respiratory system. Possible reproductive hazard. Prolonged exposure may cause chronic effects. Occupational exposure to the substance or mixture may cause adverse health effects. May cause drowsiness or dizziness.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:

TRADE SECRET SOLVENT

Hazard pictograms



Signal word

Danger

Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs (Central nervous system, Hearing organs, Kidney, Liver) through prolonged or repeated exposure.
H336	May cause drowsiness or dizziness.

Precautionary statements

Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist or vapour.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P331	Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P370 + P378	In case of fire: Use water fog, foam, dry chemical powder, carbon dioxide to extinguish.

Storage

Not assigned.

Disposal

Not assigned.

Supplemental label information

None.

2.3. Other hazards

Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
TRADE SECRET SOLVENT	57-77	TRADE SECRET TRADE SECRET	-	TRADE SECRET	#
Classification:	Flam. Liq. 3;H226, Asp. Tox. 1;H304, Acute Tox. 4;H312, Skin Irrit. 2;H315, Eye Irrit. 2;H319, Acute Tox. 4;H332, STOT SE 3;H335, STOT SE 3;H336, STOT RE 2;H373				C
TRADE SECRET SOLVENT	13-18	TRADE SECRET TRADE SECRET	-	TRADE SECRET	#
Classification:	Flam. Liq. 2;H225, Asp. Tox. 1;H304, Acute Tox. 4;H332, STOT RE 2;H373, Aquatic Chronic 3;H412				
TRADE SECRET SOLVENT	3.2-8.2	TRADE SECRET	-	-	
Classification:	-				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
TRADE SECRET SOLVENT	<1	TRADE SECRET TRADE SECRET	-	TRADE SECRET	#
Classification:	Flam. Liq. 2;H225, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Repr. 2;H361d, STOT RE 2;H373				
TRADE SECRET SOLVENT	2-7	TRADE SECRET TRADE SECRET	-	-	
Classification:	Repr. 2;H361, Aquatic Acute 1;H400				

Impurities

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
TRADE SECRET SOLVENT	<0.1	TRADE SECRET TRADE SECRET	-	TRADE SECRET	

List of abbreviations and symbols that may be used above

#: This substance has workplace exposure limit(s).

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all H-statements is displayed in section 16. Components not listed are either non-hazardous or are below reportable limits.

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed Aspiration may cause pulmonary oedema and pneumonitis. Narcosis. Dizziness. Nausea, vomiting. Abdominal pain. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Oedema. Jaundice. Prolonged exposure may cause chronic effects. May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

For emergency responders Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Use water spray to reduce vapours or divert vapour cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapour. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

7.3. Specific end use(s) Lab Marking Ink

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
TRADE SECRET SOLVENT (CAS TRADE SECRET)	STEL	552 mg/m3
		441 mg/m3
		384 mg/m3
		125 ppm
	TWA	100 ppm
		100 ppm
		441 mg/m3
		220 mg/m3
		191 mg/m3
		50 ppm
		50 ppm
		100 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Impurities	Type	Value
TRADE SECRET SOLVENT (CAS TRADE SECRET)	STEL	1080 mg/m ³
	TWA	250 ppm 430 mg/m ³ 100 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
TRADE SECRET SOLVENT (CAS TRADE SECRET)	STEL	884 mg/m ³
	TWA	442 mg/m ³ 384 mg/m ³ 200 ppm 100 ppm 100 ppm 442 mg/m ³ 221 mg/m ³ 192 mg/m ³ 50 ppm 50 ppm 100 ppm

Biological limit values**UK. EH40 Biological Monitoring Guidance Values (BMGVs)**

Components	Value	Determinant	Specimen	Sampling time
TRADE SECRET SOLVENT (CAS TRADE SECRET)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines**UK EH40 WEL: Skin designation**

TRADE SECRET SOLVENT (CAS TRADE SECRET) Can be absorbed through the skin.
Can be absorbed through the skin.
Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection	No specific recommendations due to the small quantities handled. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Colour	Red.
Odour	Xylene.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 110 °C (> 230 °F)
Flash point	27.0 °C (80.6 °F) Closed cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.88 - 0.9 (H2O=1)
Solubility(ies)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information Not relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong acids. Strong oxidising agents. Halogens.
10.6. Hazardous decomposition products	Thermal decomposition of this product can generate carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
----------------------------	--

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms	Aspiration may cause pulmonary oedema and pneumonitis. Narcosis. Dizziness. Nausea, vomiting. Abdominal pain. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Oedema. Jaundice. May cause drowsiness or dizziness.
-----------------	---

11.1. Information on toxicological effects

Acute toxicity	Harmful if inhaled. Harmful in contact with skin.
-----------------------	---

Components	Species	Test results
------------	---------	--------------

TRADE SECRET SOLVENT (CAS TRADE SECRET)

Acute

Dermal

LD50	Rabbit	15400 mg/kg 12200 mg/kg
------	--------	----------------------------

Inhalation

Vapour

LC50	Rat	28.1 mg/l, 4 Hours
LC50	Rat	17.4 mg/l, 4 hours

Oral

LD50	Rat	3500 - 4700 mg/kg 3523 mg/kg
------	-----	---------------------------------

Skin corrosion/irritation	Causes skin irritation.
----------------------------------	-------------------------

Serious eye damage/eye irritation	Causes serious eye irritation.
--	--------------------------------

Respiratory sensitisation	Based on available data, the classification criteria are not met.
----------------------------------	---

Skin sensitisation	Based on available data, the classification criteria are not met.
---------------------------	---

Germ cell mutagenicity	Based on available data, the classification criteria are not met.
-------------------------------	---

Carcinogenicity	Based on available data, the classification criteria are not met.
------------------------	---

IARC Monographs. Overall Evaluation of Carcinogenicity

TRADE SECRET SOLVENT (CAS TRADE SECRET)	2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans.
---	--

Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.
------------------------------	--

Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
---	--

Specific target organ toxicity - repeated exposure	May cause damage to organs (Central nervous system, Hearing organs, Kidney, Liver) through prolonged or repeated exposure.
---	--

Aspiration hazard	May be fatal if swallowed and enters airways.
--------------------------	---

Mixture versus substance information	No information available.
---	---------------------------

Other information	Symptoms may be delayed.
--------------------------	--------------------------

SECTION 12: Ecological information

12.1. Toxicity	Based on available data, the classification criteria are not met for hazardous to the aquatic environment.
-----------------------	--

Components	Species	Test results
------------	---------	--------------

TRADE SECRET SOLVENT (CAS TRADE SECRET)

Aquatic

Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2.6 mg/l, 96 hours
------	------	---	--------------------

Components			Species	Test results
<i>Acute</i>				
Crustacea	EC50		Daphnia magna	11.5 mg/l, 48 hours
			Water flea (Daphnia magna)	1.81 - 2.38 mg/l, 48 hours
Fish	LC50		Oncorhynchus kisutch	5.5 mg/l, 96 hours
			Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4.2 mg/l, 96 hours
<i>Chronic</i>				
Crustacea	EC50		Ceriodaphnia dubia	3.6 mg/l, 7 days
	NOEC		Ceriodaphnia dubia	0.74 mg/l, 7 days
Fish	NOEC		Oncorhynchus kisutch	1.4 mg/l, 40 days

12.2. Persistence and degradability

12.3. Bioaccumulative potential Has moderate potential to bioaccumulate.

Partition coefficient n-octanol/water (log Kow)

TRADE SECRET SOLVENT	2.73
	3.15
	3.2
	2.95
TRADE SECRET SOLVENT (CAS 100-42-5)	

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not available.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1307
14.2. UN proper shipping name	XYLENES
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	30
Tunnel restriction code	D/E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1307
14.2. UN proper shipping name	XYLENES

14.3. Transport hazard class(es)

Class 3
Subsidiary risk -
Label(s) 3

14.4. Packing group III

14.5. Environmental hazards No.

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number UN1307

14.2. UN proper shipping name XYLENES

14.3. Transport hazard class(es)

Class 3
Subsidiary risk -
Label(s) 3

14.4. Packing group III

14.5. Environmental hazards No.

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number UN1307

14.2. UN proper shipping name Xylenes

14.3. Transport hazard class(es)

Class 3
Subsidiary risk -

14.4. Packing group III

14.5. Environmental hazards No.

ERG Code 3L

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

14.1. UN number UN1307

14.2. UN proper shipping name XYLENES

14.3. Transport hazard class(es)

Class 3
Subsidiary risk -

14.4. Packing group III

14.5. Environmental hazards

Marine pollutant No.

EmS F-E, S-D

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended
Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended
Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

TRADE SECRET SOLVENT (CAS TRADE SECRET)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

TRADE SECRET SOLVENT (CAS TRADE SECRET)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

STEL: Short term exposure limit.

TWA: Time weighted average.

References

IARC Monographs. Overall Evaluation of Carcinogenicity (Volumes 1-106)

GESTIS Substance Database

HSDB® - Hazardous Substances Data Bank

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Aspen Surgical Products, Inc cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.