


**PRODUCT CODE: 141008****Acetic Acid glacial (USP, BP, Ph. Eur.) pure, pharma grade**

C₂H₄O₂
CH₃COOH



M.= 60,05

CAS [64-19-7]

EINECS 200-580-7

TARIC 2915 21 00 10

PHYSICAL DATA: liquid, Miscible with water • Hygroscopic • D 20/4 1,05 • M.P.: 16,7 °C • B.P.: 117 - 119 °C • pH(50 g/l)20 °C 2,5 • n₂₀/D : 1,3718 • Flash P.:40 °C • Ign. T.:485 °C • Vap. press. (20 °C) 15,4 hPa • Viscosity 25 °C 1,14 mPa.s • D. M. 20 °C 1,5 Debye • Dielec. constant20 °C 6,1 • Evap. number (DIN 53170) 24 • Heat evap. 118 °C 665 KJ/Kg • Satur. conc. 20 °C 38 g/m³ • Expl. limit6 %(V)17 %(V) •

BIBLIOGRAPHY: Merck Index **13**, 56 14, 55 Sax **AAT250** • Safety **2** , **13 A** • Römp **8** , **1185** • Kühn-Birett **E 6** • Beilstein **2** , **96 IV** , **94** • BRN 506007 • Fieser **25 53 71 81** • ACS **XI** • ISO 6353/2- 1983 R - 1, 2 • BP.**2020** • USP **42** • Ph. Eur. **9.0** (2017) **10.0** (2020) • F.C.C **10 11** • BOE **243**(8-10-2009) •

HAZARDOUS: C.E: 607-002-00-6 • RTECS: AF 1225000 • LD50 oral rat 3.310 mg/kg • LC50 rat 40 mg/l / 4h • VLA-EC 15 ppm37 mg/m³ VLA-ED 10 ppm25 mg/m³ EU ELV, Time weighted average: 10 ppm25 mg/m³

Derived No Effect Level (DNEL)

Workers Inhalation, acute (local) 25 mg/m³ Workers Inhalation, long term (local) 25 mg/m³ Population Inhalation, acute (local) 25 mg/m³ Population Inhalation, long term (local) 25 mg/m³

Predicted No Effect Concentration (PNEC)

Water 3.058mg/l Soil 0.478mg/kg bw/24h Sediment 11.36mg/kg bw/24h Sewage treatment plant 85mg/l



H: H226 • H314 •

P: P210 • P233 • P240 • P241 • P242 • P501 • P243 • P260 • P264 • P280 • P301+P330+P331 • P303+P361+P353 • P304+P340 • P305+P351+P338 • P310 • P338 • P363 • P370+P378 • P403+P235 •

TRANSPORT REGULATIONS: UN: 2789 • ADR: 8(3)/II • IMDG: 8(3)/II • IATA: 8(3)/II • PAX: 851 • CAO: 855 • (D/E) •

WEIGHT/VOLUME INFORMATION: 1l~1,052 kg 1kg~0,951 l

SPECIFICATIONS:

Assay (Acidim.)	99,5-100,5%
Identity :	
Identity according to Pharmacopoeias:	passes test
Freezing point	>= 15,6°C

Maximum limit of impurities

Appearance of the substance	passes test
Insoluble matter in H ₂ O	passes test
Non-volatile matter	0,005 %
Reducing substances	passes test
Easily oxidable substances	passes test
Chloride (Cl)	0,001%
Sulfate (SO ₄)	0,001%
Residual solvents (Ph.Eur/USP)	passes test
Aldehydes (as CH ₃ CHO)	0,05%

Fe	0,0005 %
----	----------

Elemental impurities (ICH Q3D):

Class 1

Cd	0,5 ppm
Pb	0,5 ppm
As	1 ppm
Hg	1,5 ppm

Class 2A

Co	5 ppm
V	10 ppm
Ni	20 ppm

Class 2B

Tl	0,8 ppm
Au	10 ppm
Pd	10 ppm
Ir	10 ppm
Os	10 ppm
Rh	10 ppm
Ru	10 ppm
Se	15 ppm
Ag	15 ppm
Pt	10 ppm

Class 3

Li
Sb
Ba
Mo
Cu
Sn
Cr

55 ppm
120 ppm
140 ppm
25 ppm
250 ppm
600 ppm
25 ppm

Ed.: 9 . Vig.: 14.06.2019 .

Prod.: 141008

DOMINIQUE DUTSCHER SAS