HyFlex® 11-625 11-627 11-628

MECHANICAL PROTECTION



STYLE #	CONSTRUC- TION	GAUGE	LINER Material	COATING Material	FINISHING	CUFF STYLE	COLOUR	EN SIZE	LENGTH MM	PACKAGING
11-625	Knitted	15	Spandex Dyneema®	Polyurethane	Palm coated	Knitwrist	White	6, 7, 8, 9, 10, 11	210 - 255	12 pairs in a bag, 12 bags in a carton
11-627	Knitted	15	Nylon Lycra® Dyneema®	Polyurethane	Palm coated	Knitwrist	Grey	6, 7, 8, 9, 10, 11	210 - 270	12 pairs in a bag, 12 bags in a carton
11-628	Knitted	15	Nylon Lycra® Dyneema®	Polyurethane	Palm coated	Long knitwrist	Grey	6, 7, 8, 9, 10, 11	270 - 320	12 pairs in a bag, 12 bags in a carton







Dexterity with superb cut resistance for optimal productivity

PRIMARY INDUSTRIES













IDEAL APPLICATIONS

- Glass manufacturing
- Aeronautics

- Assembly of white goods
 Plastics injection and moulding
 Assembling metal parts and components
 Handling of sharp-edged objects, preassembling, cutting of small dry or lightly oiled
- parts and maintenance. Finishing works

DESCRIPTION

- The HyFlex® 11-625, 11-627 and 11-628 gloves deliver a perfect balance of comfort and sure handling with superior cut resistance.
- The liners have an innovative yarn structure that contains an optimal rate of Dyneema®. This offers high levels of cut resistance, for a safe use in controlling, handling and assembly applications involving contacts with sharp pieces.

 The Lycra® in the liners of both gloves, as well as the polyurethane coating, provides excellent flexibility and fit.
- The three models are designed for use in dry, as well as slightly oily environments.


REMARKS

• 11-625 & 11-627: Fit for special purpose

FEATURED TECHNOLOGY

Dyneema®

Dyneema'



CATEGORY II

Print date: 23-05-2017



Riverside Business Park, Block J Boulevard International 55, 1070 Brussels, Belgium Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03 http://www.ansell.eu • E-mail info@ansell.eu

