SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : mikrozid® universal liquid

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Disinfectants and general biocidal products

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Producer :
Schülke & Mayr GmbH
Robert-Koch-Str. 2

22851 Norderstedt
Germany
Telephone: +49 (0)40/ 52100-0
Telefax: +49 (0)40/ 52100318
mail@schuelke.com
www.schuelke.com

Supplier :
Schülke & Mayr UK Ltd.
Cygnet House
1, Jenkin Road, Meadowhall

Sheffield S9 1AT
United Kingdom
Telephone: +44 114 254 35 00
Telefax: +44 114 254 35 01
mail.uk@schulke.com

E-mail address of person responsible for the SDS/Contact person :
Application Specialists
+49 (0)40/ 521 00 666
AD@schuelke.com
(Schülke & Mayr UK Ltd.: +44-1142543500)

1.4 Emergency telephone number

Emergency telephone number : Carechem 24 International:+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019)

Hazard pictograms :



Signal word : Warning

Hazard statements :
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements :
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Has a degreasing effect on the skin.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solution of the following substances with harmless additives.

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)

	Index-No. Registration number		
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 10 - < 20
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Take off all contaminated clothing immediately.

If inhaled : Move to fresh air.
If symptoms persist, call a physician.

In case of skin contact : Wash with water and soap as a precaution.
If symptoms persist, call a physician.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If eye irritation persists, consult a specialist.

If swallowed : Do NOT induce vomiting.
Rinse mouth with water.
Give small amounts of water to drink.
Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Treat symptomatically.

Risks : Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry powder
Alcohol-resistant foam

Water spray jet
Carbon dioxide (CO2)

Unsuitable extinguishing media : Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : Avoid subsoil penetration.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

see Section 8 + 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only in well-ventilated areas.
Wear personal protective equipment.

Advice on protection against fire and explosion : The hot product gives off combustible vapours. Keep away from sources of ignition - No smoking.

Hygiene measures : Keep away from food and drink.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store at room temperature in the original container.

Further information on storage conditions	:	Keep away from direct sunlight. Keep container tightly closed. Recommended storage temperature: 15 - 25°C
Advice on common storage	:	Do not store together with explosives, oxidizing agents, organic peroxides and infectious products.

7.3 Specific end use(s)

Specific use(s) : none

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m3	GB EH40
		STEL	500 ppm 1,250 mg/m3	GB EH40
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m3	GB EH40

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
propan-2-ol	Workers	Skin contact	Long-term systemic effects	888 mg/kg
	Workers	Inhalation	Long-term systemic effects	500 mg/m3
ethanol	Workers	Inhalation	Acute local effects	1900 mg/m3
	Workers	Skin contact	Long-term systemic effects	343 mg/kg
	Workers	Inhalation	Long-term systemic effects	950 mg/m3

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
propan-2-ol	Fresh water	140.9 mg/l
	Marine water	140.9 mg/l
	Fresh water sediment	552 mg/kg
	Marine sediment	552 mg/kg
	Soil	28 mg/kg
	Intermittent use/release	140.9 mg/l
	Effects on waste water treatment plants	2251 mg/l
	Oral	160 mg/kg food
ethanol	Fresh water	0.96 mg/l
	Marine water	0.79 mg/l
	Fresh water sediment	3.6 mg/kg
	Soil	0.63 mg/kg
	Marine sediment	2.9 mg/kg

	Sewage treatment plant	580 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166
Hand protection		
Directive	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
Remarks	:	Prolonged contact: Nitrile rubber gloves e.g. Camatril (>120 Min., layer thickness: 0.40 mm) or butyl rubber gloves e.g. Butoject (>480 Min., layer thickness: 0.70 mm) made by KCL or gloves from other manufacturers offering the same protection.
Skin and body protection	:	Work uniform or laboratory coat.
Respiratory protection	:	No personal respiratory protective equipment normally required.
Protective measures	:	Avoid contact with eyes.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	colourless
Odour	:	alcohol-like
Odour Threshold	:	not determined
pH	:	ca. 3.5 Concentration: 100 %
Melting point/freezing point	:	< -5 °C
Decomposition temperature		No data available
Boiling point/boiling range	:	ca. 80 °C
Flash point	:	26 °C Method: DIN 51755 Part 1
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Sustains combustion
Upper explosion limit / Upper	:	12 %(V)

flammability limit		Raw material
Lower explosion limit / Lower flammability limit	:	2 %(V) Raw material
Vapour pressure	:	ca. 40 hPa (20 °C)
Relative vapour density	:	No data available
Density	:	ca. 0.95 g/cm3
Solubility(ies)		
Water solubility	:	completely soluble (20 °C)
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	425 °C Raw material
Viscosity		
Viscosity, dynamic	:	not determined
Explosive properties	:	No data available
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Metal corrosion rate	:	None reasonably foreseeable.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid	:	Strong acids and oxidizing agents

10.6 Hazardous decomposition products

None reasonably foreseeable.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

propan-2-ol:

Acute oral toxicity	:	LD50 (Rat): 5,840 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 39 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): 13,900 mg/kg Method: OECD Test Guideline 402

ethanol:

Acute oral toxicity	:	LD50 (Mouse): 8,300 mg/kg
Acute inhalation toxicity	:	LC50 (Mouse): 39 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): 20,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Method	:	Expert judgement and weight of evidence determination.
Result	:	No skin irritation
Remarks	:	largely based on human evidence

Components:

propan-2-ol:

Result	:	No skin irritation

ethanol:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

propan-2-ol:

Result	:	Eye irritation

ethanol:

Method	:	OECD Test Guideline 405
Result	:	Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

propan-2-ol:

Test Type	:	Buehler Test
Species	:	Guinea pig
Result	:	Did not cause sensitisation on laboratory animals.

ethanol:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

propan-2-ol:

Genotoxicity in vitro	:	Test Type: Ames test Method: Mutagenicity (Escherichia coli - reverse mutation assay) Result: Non mutagenic
Genotoxicity in vivo	:	Species: Mouse Method: Mutagenicity (micronucleus test) Result: Non mutagenic
Germ cell mutagenicity- Assessment	:	Not mutagenic in Ames Test

ethanol:

Genotoxicity in vitro	:	Test Type: Microbial mutagenesis assay (Ames test) Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation

		Method: OECD Test Guideline 471 Result: Not mutagenic in Ames Test
Genotoxicity in vivo	:	Result: Non mutagenic
Germ cell mutagenicity- Assessment	:	Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Not classified based on available information.

Components:

propan-2-ol:

Remarks	:	Based on available data, the classification criteria are not met.

ethanol:

Carcinogenicity - Assessment	:	Did not show carcinogenic effects in animal experiments.

Reproductive toxicity

Not classified based on available information.

Components:

propan-2-ol:

Effects on foetal development	:	Species: Rat Application Route: Oral General Toxicity Maternal: NOAEL: 400 mg/kg body weight
Reproductive toxicity - Assessment	:	Based on available data, the classification criteria are not met.

ethanol:

Effects on foetal development	:	Species: Rat Application Route: Oral General Toxicity Maternal: NOAEL: 2,000 mg/kg body weight
Reproductive toxicity - Assessment	:	Animal experiments showed mutagenic and teratogenic effects.

STOT - single exposure

Not classified based on available information.

Components:

propan-2-ol:

Assessment	:	May cause drowsiness or dizziness.

ethanol:

Remarks	:	No data available

STOT - repeated exposure

Not classified based on available information.

Components:

propan-2-ol:

Remarks	:	Based on available data, the classification criteria are not met.

ethanol:

Remarks	:	No data available

Repeated dose toxicity

Components:

propan-2-ol:

Remarks	:	No data available

ethanol:

Species	:	Rat
NOAEL	:	1,730 mg/kg
LOAEL	:	3,160 mg/kg
Application Route	:	Oral
Exposure time	:	90 d

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks	:	No human information is available.

SECTION 12: Ecological information

12.1 Toxicity

Components:

propan-2-ol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 10,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 72 h Test Type: static test

		EC50 (green algae): 1,800 mg/l Exposure time: 7 d

ethanol:

Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 8,140 mg/l Exposure time: 48 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 5,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	IC50 (Scenedesmus quadricauda (Green algae)): > 100 mg/l Exposure time: 72 h

12.2 Persistence and degradability

Components:

propan-2-ol:

Biodegradability	:	Result: Readily biodegradable.

ethanol:

Biodegradability	:	Test Type: aerobic Result: Readily biodegradable. Biodegradation: > 70 % Exposure time: 5 d Method: OECD 301D / EEC 84/449 C6

12.3 Bioaccumulative potential

Components:

propan-2-ol:

Bioaccumulation	:	Remarks: No bioaccumulation is to be expected (log Pow <= 4).
Partition coefficient: n-octanol/water	:	log Pow: 0.05 (20 °C) Method: OECD Test Guideline 107

ethanol:

Bioaccumulation	:	Remarks: Bioaccumulation is unlikely.
Partition coefficient: n-octanol/water	:	log Pow: -0.14 Method: Calculated value

12.4 Mobility in soil

Components:

propan-2-ol:

Mobility	:	Remarks: Mobile in soils

ethanol:

Mobility	:	Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	:	No data is available on the product itself.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR	:	UN 1987
IMDG	:	UN 1987
IATA	:	UN 1987

14.2 UN proper shipping name

ADR	:	ALCOHOLS, N.O.S. (propan-2-ol, ethanol)
IMDG	:	ALCOHOLS, N.O.S. (propan-2-ol, ethanol)
IATA	:	Alcohols, n.o.s. (propan-2-ol, ethanol)

14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)

IMDG

Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-D

IATA (Cargo)

Packing instruction (cargo aircraft)	:	366
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable liquid

IATA (Passenger)

Packing instruction (passenger aircraft)	:	355
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable liquid

14.5 Environmental hazards

ADR

Environmentally hazardous	:	no

IMDG

Marine pollutant	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 29.23 %
according to Detergents Regulation EC 648/2004	:	less than 5 %: Anionic surfactants

The components of this product are reported in the following inventories:

TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	Product contains substance(s) not listed on TSCA inventory.
AIIC	:	Not in compliance with the inventory
DSL	:	This product contains the following components that are not on the Canadian DSL nor NDSL. Sulfonic acids, C14-17-sec-alkane, sodium salts
ENCS	:	Not in compliance with the inventory
ISHL	:	Not in compliance with the inventory
KECI	:	Not in compliance with the inventory
PICCS	:	Not in compliance with the inventory
IECSC	:	Not in compliance with the inventory
NZIoC	:	Not in compliance with the inventory
TECI	:	On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

Exempt

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		**Classification procedure:**
Flam. Liq. 3	H226	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.