BRAND



Transferpette® electronic

Ergonomics for fatigue-free operation

BRAND. For lab. For life.®

+ Ergonomic, handy design
+ Clear and intuitive operation
+ Up to 4,000 pipetting cycles on a single charge

DOMINIQUE DUTSCHER SAS

ELECTRONIC MICROPIPETTES



DOMINIQUE DUTSCHER SAS

Get to know the Transferpette® electronic

Ergonomic

If you pipette long series using electronic pipettes, work efficiency and the ergonomics of the instrument are paramount. The Transferpette® electronic micropipette is the perfect solution for efficiency and ergonomics, with its impressive easy and uncomplicated operational concept. The low weight, intuitive arrangement of control elements and balanced weight distribution of the Transferpette® electronic ensure fatigue-free operation and minimize the risk of RSI (repetitive strain injury). In addition, the adjustable finger rest allows every user, whether left- or right-handed, to fine tune the instrument for an ergonomically natural positioning of the hand in relation to the functional elements.

Simple and intuitive

Five functions are available for different applications and media: pipetting, mixing, reverse pipetting, pipetting for electrophoresis and dispensing. The operational concept for these functions is very simple: all functions are controlled by the four buttons under the clear display and then activated by the large, ergonomically positioned pipetting button.
The Transferpette® electronic draws its energy from a NiMH battery. One battery charge allows over 4.000 pipetting cycles. During the charging process, you can continue to pipette with the 1-meter charging cable plugged in. The battery refresh function provides a regeneration function for increasing the performance and extending the life of the battery.

Easy maintenance and calibration

If readjustment is necessary after calibration, this can be done quickly and easily and without tools using the Easy Calibration technology.
On multi-channel instruments, the individual shafts and pistons with seals can be easily disassembled. As a result, the shafts and seals are easy to clean or replace.

DOMINIQUE DUTSCHER SAS



Transferpette® electronic–single-channel
Volume range of single-channel pipette models:
from 0.5 µl to 5000 µl



Transferpette® electronic–multi-channel
Volume range of multi-channel pipette models:
from 0.5 µl to 1250 µl

- \+ Universal tip cone
- \+ Pipette shaft (pipetting unit) can be removed and is completely autoclavable (121 °C)
- \+ Individual pipette shafts on multichannel pipettes are easy to replace

Overview: the advantages of the Transferpette® electronic

The Transferpette® electronic single-channel pipette is available in 5 different models: 0.5 – 10 µl, 2 – 20 µl, 10 – 200 µl, 50 – 1000 µl and 250 – 5000 µl.
The Transferpette®-8 / -12 electronic multi-channel pipette is available in 6 volume ranges: 0.5 – 10 µl, 1 – 20 µl, 5 – 100 µl, 10 – 200 µl, 15 – 300 µl, 50 – 1250 µl.

Handy design (form follows function), balanced weight distribution, pleasant housing material, intuitive software and user-friendly technical documentation were the focus of attention during development of the Transferpette® electronic as an overall ergonomic concept. The result is an inherently logical and self-explanatory operating principle.

Charging socket

One battery charge allows over 4.000 pipetting cycles.



Transferpette® electronic

Finger rest

Individually adjustable

Hand grip


Slim, ergonomic shape


Color-coded nominal volume

For quick visual confirmation

Removable pipette shaft

Completely autoclavable (121 °C) pipette shaft





DOMINIQUE DUTSCHER SAS

The multi-channel pipettes Transferpette®-8 and -12 electronic



Transferpette®-12 electronic

Display

Clear and simple

Intuitive operation

All functions with 4 buttons.



Transferpette®-8 electronic

Adaptable

Pipetting unit can be rotated by 360° to accommodate individual preferences.

Minimal effort

Easy insertion and ejection of tips due to O-rings.

Easy cleaning and maintenance

Individual shafts and seals are easy to remove, making cleaning and replacement simple.

DOMINIQUE DUTSCHER SAS

PROGRAMS on page 11



Adjustable finger rest



Pipetting with electrophoresis (GEL-mode). Program for loading electrophoresis gels.



Easy maintenance



Adjustment without tools with the Easy Calibration technology

The right pipette for your applications



Transferpette® electronic

Items supplied: each Transferpette® electronic pipette has DE-M marking and is supplied with performance certificate, battery, AC adapter, silicone grease

	Capacity, µl (color-coded)			Subdivision µl	A* ≤ ± %	µl	CV* ≤ %	µl	With AC adapter for	Cat. No.
●	0.5	–	10	0.01	1.0	0.1	0.4	0.04	Europe (continental)	705299
									UK/Ireland	705309
									USA / Japan	705319
									Australia	705329
									without AC adapter	705339
●	2	–	20	0.02	1.0	0.2	0.4	0.08	Europe (continental)	705300
									UK/Ireland	705310
									USA / Japan	705320
									without AC adapter	705340
●	10	–	200	0.2	0.8	1.6	0.2	0.4	Europe (continental)	705303
									UK / Irland	705313
									USA / Japan	705323
									Australia	705333
									without AC adapter	705343
●	50	–	1000	1.0	0.6	6	0.2	2.0	Europe (continental)	705306
									UK / Irland	705316
									USA / Japan	705326
									Australia	705336
									without AC adapter	705346
●	250	–	5000	5.0	0.6	30	0.2	10	Europe (continental)	705307
									UK / Irland	705317
									USA / Japan	705327
									Australia	705337
									without AC adapter	705347

* Calibrated to deliver (TD, Ex). Error limits according to the nominal capacity (= maximum volume) indicated on the instrument, obtained with instrument and distilled water at equilibrium with ambient temperature at 20 °C, and with smooth, steady operation. The error limits are well within the limits of DIN EN ISO 8655-2.
DE-M marking. A = Accuracy, CV = Coefficient of variation

Notice: When ordering instruments with DAkkS calibration certificates, the prefix 'DAkkS' must be added to the order number, e.g., DAkkS 7052 99. BRAND also offers calibration service at the factory lab.

All product information
can be found at **shop.brand.de**

DOMINIQUE DUTSCHER SAS

Items supplied: Transferpette®-8 or -12 electronic, battery pack, 1 reagent reservoir, grease

Nominal volume	Further accessories
up to 300 µl	Region-specific power supply unit with battery charging cable, 1 instrument stand, 1 x TipBox, 1 x TipRack refill pack, 1 set of O-rings made of FKM/silicone
1250 µl	Universal power adapter with battery charging cable, 2 x TipBox, 1 support frame, 1 shelf/rack mount, 1 set of O-rings made of silicone additionally 1x individual stand for 705397 and 705447

Transferpette®-8 electronic



Capacity, µl (color-coded)	Subdivision µl	A* ≤ ± %	µl	CV* ≤ %	µl	With AC adapter for	Cat. No.
0.5 – 10	0.01	1.2	0.12	0.8	0.08	Europe (continental) UK / Ireland USA / Japan	705399 705409 705419
1 – 20	0.02	1.0	0.2	0.5	0.1	Europe (continental) UK / Ireland USA / Japan	705400 705410 705420
5 – 100	0.1	0.8	0.8	0.25	0.25	Europe (continental) UK / Ireland USA / Japan Australia	705403 705413 705423 705433
10 – 200	0.2	0.8	1.6	0.25	0.5	Europe (continental) UK / Ireland USA / Japan Australia	705404 705414 705424 705434
15 – 300	0.5	0.8	2.4	0.25	0.75	Europe (continental) UK / Ireland USA / Japan Australia	705406 705416 705426 705436
50 – 1250	1.0	1.0	12.5	0.25	3.125	universal power adapter	705397 705398

Transferpette®-12 electronic



Capacity, µl (color-coded)	Subdivision µl	A* ≤ ± %	µl	CV* ≤ %	µl	With AC adapter for	Cat. No.
0.5 – 10	0.01	1.2	0.12	0.8	0.08	Europe (continental) UK / Ireland USA / Japan	705449 705459 705469
1 – 20	0.02	1.0	0.2	0.5	0.1	Europe (continental) UK / Ireland USA / Japan Australia	705450 705460 705470 705480
5 – 100	0.1	0.8	0.8	0.25	0.25	Europe (continental) UK / Ireland USA / Japan	705453 705463 705473
10 – 200	0.2	0.8	1.6	0.25	0.5	Europe (continental) UK / Ireland USA / Japan Australia	705454 705464 705474 705484
15 – 300	0.5	0.8	2.4	0.25	0.75	Europe (continental) UK / Ireland USA / Japan	705456 705466 705476
50 – 1250	1.0	1.0	12.5	0.25	3.125	universal power adapter	705447 705448

DOMINIQUE DUTSCHER SAS



DOMINIQUE DUTSCHER SAS

Accessories for simple and efficient work

Original Transferpette® electronic accessories ensure optimal work conditions in the laboratory. With holders and stands, the devices are always properly stored and close at hand for the next application.



Wall mount

For all Transferpette® electronic single- and multi-channel pipettes

Pack of	Cat. No.
1	705382



Shelf / rack mount

For all Transferpette® electronic single- and multi-channel pipettes

Pack of	Cat. No.
1	705383



Single stand Transferpette® electronic

For all Transferpette® electronic single- and multi-channel pipettes

Description	Pack of	Cat. No.
all sizes	1	705384



Charging stand

Up to 3 single-channel pipettes (up to 1000 µl) can be charged simultaneously in the charging stand. Individual power supplies can then be dispensed with.

Description	Pack of	Cat. No.
Europe	1	705390
UK / Ireland	1	705391
USA / Japan	1	705392



Single stand Transferpette® electronic

For all Transferpette® electronic single-channel pipettes

Description	Pack of	Cat. No.
up to 1000 µl	1	705385
250 – 5000 µl	1	705386



Single stand

For all Transferpette® multi-channel pipettes up to 300 µl

Pack of	Cat. No.
1	703440

All information on the product and accessories at shop.brand.de

DOMINIQUE DUTSCHER SAS

The right pipette tip for your Transferpette® electronic

Optimal results are achieved in combination with BRAND pipette tips and filter tips.
Our bulk packed tips as well as the 5 and 10 ml tips have the CERTIFIED LIFE SCIENCE QUALITY. All racked pipette tips and filter tips up to 1250 µl meet the quality level BIO-CERT® LIQUID HANDLING QUALITY.

BRAND offers a full tip system for any application requirement. In addition, tips from many other manufacturers can be used with the Transferpette® electronic. More detailed information is available on request.



Pipette tips Filter tips Volume range	Transferpette® electronic single-channel Nominal volume					Transferpette® electronic multi-channel Nominal volume					
	10 µl	20 µl	200 µl	1000 µl	5000 µl	10 µl	20 µl	100 µl	200 µl	300 µl	1250 µl
0.1 – 20 µl	✓2)	✓2)				✓	✓				
0.5 – 20 µl	✓	✓				✓	✓				
1 – 50 µl	✓	✓				✓	✓				
2 – 200 µl [1]			✓					✓	✓	✓	
5 – 300 µl			✓					✓	✓	✓	
50 – 1000 µl [1]				✓							
50 – 1250 µl [3]				✓2)							✓
50 – 1250 µl XL [3]				✓2)							✓2)
0.5 – 5 ml					✓						
1 – 10 ml											
0.1 – 1 µl	✓2)					✓					
0.5 – 10 µl	✓	✓				✓	✓				
1 – 20 µl	✓	✓				✓	✓				
2 – 20 µl			✓					✓	✓		
5 – 100 µl			✓					✓	✓	✓	
5 – 200 µl			✓					✓	✓	✓	
50 – 1000 µl				✓							
50 – 1250 µl [3]				✓2)							✓
50 – 1250 µl XL [3]				✓2)							✓2)

✓ = Tip volume less than pipette's nominal volume
1) Bulk tips are yellow or blue colored; racked tips are colorless in a yellow-colored or blue-colored tip tray
2) Calibration and possible adjustment needed
3) 1250 µl = Length 86 mm, 1250 µl XL = Length 102 mm



TipBox



Transfer aid



TipRacks



TipBox 1250 µl with support frame

All information on tips at **shop.brand.de**

DOMINIQUE DUTSCHER SAS


USER TIP

Programs

Besides pipetting comfort, an important design goal for the Transferpette® electronic was rapid and intuitive work, and simple, fast program changes. The objective was to gain the advantages of electronic operation with no trade-offs.




* The GEL mode is not included for single-channel and multi-channel pipettes with nominal volume from 1000 µl because these volumes are rarely used in electrophoresis.



Pipetting (PIP Mode)

The 'standard' program. The set volume is aspirated by the pipette, and then discharged.



Mixing of Samples (PIPmix Mode)

Program for mixing of liquids. The sample is repeatedly aspirated and discharged, and the number of mixing cycles is displayed.



Reverse Pipetting (revPIP Mode)

Program specially designed for the pipetting of liquids with a high viscosity, high vapor pressure or foamy media.




Pipetting with Electrophoresis (GEL Mode)*

Program for the loading of electrophoresis gels. The required sample volume is aspirated at the desired, adjustable speed, and is then discharged very slowly. The exact volume of liquid discharged is shown in the display as it is discharged.



Dispensing (DISP Mode)

A program for the dispensing of liquids in a series of equal aliquots. A volume that has been aspirated is dispensed in steps.



Easy Calibration Technique (CAL Mode)

Every laboratory that is certified according to ISO 9001 or accredited according to ISO/IEC 17 025 or works according to the GLP/GMP guidelines must regularly calibrate its testing equipment and adjust as necessary.
Program for making quick adjustments to the instrument, without tools. By changing the factory setting, <CAL> appears automatically in the display. The factory setting can be restored at any time.



Battery-Refresh (batt Mode)

Regeneration function for increased performance and extending the service life of the batteries. The world's first microliter pipette with this function.

DOMINIQUE DUTSCHER SAS

BRAND GMBH + CO KG
P.O. Box 1155 | 97861 Wertheim | Germany
T +49 9342 808 0 | F +49 9342 808 98000 | info@brand.de | www.brand.de

BRAND. For lab. For life.®

BRAND®, BRAND. For lab. For life.®, Transferpette®, as well as the BRAND figurative mark are registered trademarks or trademarks of BRAND GMBH + CO KG, Germany. The BRANDGROUP figurative mark is registered trademark or trademark of Brand Group SE & Co. KG, Germany. All other trademarks mentioned or depicted here are the property of the respective owners.

Our technical literature is intended to inform and advise our customers. However, the validity of general empirical values, and of results obtained under test conditions, for specific applications depends on many factors beyond our control. Please appreciate, therefore, that no claims can be derived from our advice. The user is responsible for checking the appropriateness of the product for any particular application.
California Residents: For more information concerning California Proposition 65, please refer to www.brand.de/calprop65.

Subject to technical modification without notice. Errors excepted.

994732 © 2022 BRAND GMBH + CO KG | Printed in Germany | 0326

Find accessories and replacement parts, user manuals, test instructions (SOP) and product videos at **shop.brand.de**

Further information on products and applications can be found on our YouTube channel: **mylabBRAND**

4 033378 424112

Renewable energy
We use 100 % certified green electricity.

Sustainable packaging
We use cardboard with approx 90 % recycled content for our product packaging.

DOMINIQUE DUTSCHER SAS

BRAND (Shanghai) Trading Co., Ltd.
Shanghai, China

T +86 21 6422 2318
info@brand.com.cn
china.brand.com.cn

BRAND Scientific Equipment Pvt. Ltd.
Mumbai, India

T +91 22 42957790
customersupport@brand.co.in
www.brand.co.in

BRANDTECH® Scientific, Inc.
Essex, CT. United States of America

T +1 860 767 2562
info@brandtech.com
www.brandtech.com

BRANDGROUP®