COOLSAFE 55-4
SPECIFICATIONS



For more information please visit:
www.labogene.com

CoolSafe 55-4	Unit	Part no 7001000060
Digital read-out of temperature		Yes
Digital read-out of pressure		No
Ultimate temperature at 20°C room temperature	°C	-55
Power requirements	V/Hz	230/50-60
Power consumption	W	500
Insulation	mm	90
Condenser capacity	kg	3
Condenser capacity per 24 hours	kg	2,5
Total volume of Condenser	L	4
Weight net	kg	40
Cabinet dimensions (DxWxH)	mm	500x400x520
Cabinet material		Polyester coated steel
Condenser material		Stainless steel AISI 316
Cooling media		R 507
Vacuum Valve		Solenoid
Draintap		Yes
Keypad for control options		No
R 485/USB port for Labogene software		No

DOMINIQUE DUTSCHER SAS

Revision date | rev. | version: May 2020 | 0.2 | CoolSafe 55-4 230V

LaboGene A/S
Bjarkesvej 5
DK-3450 Allerød

Tel (+45) 3940 2566
Fax (+45) 3995 2566
Mail info@labogene.com
Web www.labogene.com

LABOGENE
Scandinavian by Design

CERTIFIED ISO 9001 UKAS MANAGEMENT SYSTEMS 001