COOLSAFE PRO 100-9
SPECIFICATIONS



For more information please visit:
www.labogene.com

CoolSafe Pro 100-9	Unit	Part no: 7001000617
Digital read-out of temperature		Yes
Digital read-out of pressure		Yes
Ultimate temperature at 20°C room temperature	°C	-100
Power requirements	V/Hz	230/50-60
Power consumption	W	800
Insulation	mm	90
Condenser capacity	kg	7
Condenser capacity per 24 hours	kg	4
Total volume of Condenser	L	9
Weight net	kg	75
Cabinet dimensions (DxWxH)	mm	620x495x745
Cabinet material		Polyester coated steel
Condenser material		Stainless steel AISI 316
Cooling media		R 507/R170
Vacuum Valve		Solenoid
Draintap		Yes
Keypad for control options		No
R 485/USB port for Labogene software		No

DOMINIQUE DUTSCHER SAS

Revision date | rev. Iversion: May 2020 | 0.2 | CoolSafe Pro 100-9 - 230V

LaboGene A/S
Bjarkesvej 5
DK-3450 Allerød

Tel (+45) 3940 2566
Fax (+45) 3995 2566
Mail info@labogene.com
Web www.labogene.com

LABOGENE
Scandinavian by Design

CERTIFIED ISO 9001 UKAS MANAGEMENT SYSTEMS 001