xylem
Let's Solve Water




# Provide the right Temperature ...

... WITH THERMOSTATIC CABINETS FOR OxiTop®

DUPLIQUÉ DUTSCHER SAS

WTW
a xylem brand

# Provide the right temperature

- Incubation conforming to standards
- Suited for BOD, OECD 301F, soil respiration, anaerobic degradation
- Temperature adjustable in steps of 1 K between 10° and 40 °C
- Eco-friendly refrigerant R600a



TS 608-G/2-i

The new WTW® thermostatic cabinets are available in three sizes and different variants.

Note: The necessary temperature constancy will only be achieved in combination with the samples!

**TS 608/2-i**
Compact thermostatic cabinet for up two OxiTop® IS 12 stirring platforms. It is easy to integrate into the working environment and perfectly suited for standard applications. It has two internal plugs for connecting stirring platforms.

**TS 608-G/2-i**
As above but with a door made of insulation glass. Allows visual checking of the OxiTop® heads without opening the door.

**TS 700/4-i**
Thermostatic cabinet for extensive sample processing. Capable of simultaneous measurement of up to four IS 12 stirring platforms. It has four internal plugs for connecting stirring platforms.

**TS 700-G/4-i**
As TS 700/4-i but with a door made of insulation glass. Allows visual checking of the OxiTop® heads without opening the door.

**TS 1010-i**
A thermostatic cabinet for special applications. With extra space for special vessels e.g. biogas or soil respiration measurement. It has four internal plugs for connecting stirring platforms.

## Technical data and ordering information

| **Model** | **TS 608/2-i** | **TS 608-G/2-i** | **TS 700/4-i** | **TS 700-G/4-i** | **TS 1010-i** |
|---|---|---|---|---|---|
| **Order No.** | 208450 | 208452 | 208464 | 208466 | 208468 |
| **Volumen** (l) | 180 | 180 | 317 | 337 | 534 |
| **Outer dimensions** (mm) | | | | | |
| **H** | 850 | 850 | 1684 | 1684 | 1684 |
| **W** | 600 | 600 | 597 | 597 | 747 |
| **D** | 600 | 600 | 654 | 654 | 769 |
| **Inner dimensions** (mm) | | | | | |
| **H** | 702 | 702 | 1459 | 1459 | 1459 |
| **W** | 513 | 513 | 475 | 475 | 625 |
| **D** | 441 | 441 | 423 | 423 | 539 |
| **Net weight** (kg) | 34 | 43 | 53 | 69 | 69 |
| **Control range** | 10 °C … 40 °C | | | | |
| **Increment** | 1 K | | | | |
| **Temperature stability** | ±0,5 K | | | | |
| **Max. power consumption** (W) | 160 | 320 | 380 | 380 | 380 |
| **Internal sockets** | 2 | 2 | 4 | 4 | 4 |

DOMINIQUE DUTSCHER SAS

xylem
Let's Solve Water

Xylem Analytics Germany Sales GmbH & Co. KG, WTW · Am Achalaich 11 · 82362 Weilheim · Germany
Phone: +49 881 1830 · Fax: +49 881 183-420 · Info.WTW@xylem.com · www.xylemanalytics.com

All names are registered tradenames or trademarks of Xylem Inc. or one of its subsidiaries. Technical changes reserved.
© 2018 Xylem Analytics Germany Sales GmbH & Co. KG.
999253US February 2024