

Data Sheet

FIREPol[®] Master Mix with 12.5 mM MgCl₂, 5x

Cat. No.	Pack Size	20 µl rxn
04-11-00S25	0.1 ml	25
04-11-00125	1 ml	250
04-11-00125-5	5 x 1 ml	1250
04-11-00125-10	10 x 1 ml	2500

For *in vitro* use only

Description:

FIREPol[®] Master Mix is a 5x-concentrated ready-to-use solution containing all reagents required for PCR (except template, primers and water).

Applications:

- Suited for a wide range of PCR assays
- TA cloning

Mix Composition:

- FIREPol[®] DNA polymerase
- 5x Reaction Buffer B
0.4 M Tris-HCl, 0.1 M (NH₄)₂SO₄, 0.1% w/v Tween-20
- 12.5 mM MgCl₂
1 x PCR solution – 2.5 mM MgCl₂
- 1 mM dNTPs of each
1 x PCR solution – 200 µM dATP, 200 µM dCTP, 200 µM dGTP and 200 µM dTTP

Shipping and Storage conditions:

Routine storage: -18°C to -28°C

Shipping and temporary storage for up to 1 month at room temperature or storage for up to 6 months at 2-8°C has no detrimental effects on the quality of the product.

Manufactured by Solis BioDyne in compliance with the ISO 9001 and ISO 13485 certified Quality Management System.

FOR RESEARCH USE ONLY. NOT FOR USE IN DIAGNOSTIC PROCEDURES.

Recommendations:

We recommend using FIREPol[®] Master Mix in any PCR application that will be visualized by agarose gel electrophoresis and ethidium bromide staining.

In order to prevent contamination, we recommend you to setup the reaction under laminar or in PCR box.

Recommended PCR reaction mix:

Component	Volume	Final conc.
FIREPol [®] Master Mix (5x)	4 µl	1x
Forward primer (10 µM)	0.2–0.6 µl	0.1–0.3 µM
Reverse primer (10 µM)	0.2–0.6 µl	0.1–0.3 µM
DNA template	variable	variable ¹
H ₂ O	Up to 20 µl	

¹Conc. of cDNA 0.01 pg/µl -0.1 ng/µl; gDNA 0.1 ng/µl – 10 ng/µl

Recommended PCR cycles:

Operation	Temp.	Time	Cycles
Initial denaturation²	95°C	3–5 min	1
Denaturation	95°C	15–30 s	25–30
Annealing ³	54–66°C	30–60 s	
Elongation ⁴	72°C	40 s–4 min	
Final elongation	72°C	5–10 min	

² Complex templates, such as gDNA, require longer time to denature (5 min). With low complexity templates (i.e. lambda, plasmid DNA), initial denaturation time can be reduced to 3 min.

³ The annealing temperature (T_a) depends on the melting temperature (T_m) of the primers. A T_a that is about 2 to 5°C lower than the T_m of the primers is generally suitable. Performing temperature gradient is recommended.

⁴ Elongation time depends on the length of the fragment to be amplified. A time of 1 min/kb is recommended.

Safety warnings and precautions:

This product and its components should be handled only by persons trained in laboratory techniques. It is advisable to wear suitable protective clothing, such as laboratory overalls, gloves and safety glasses. Care should be taken to avoid contact with skin or eyes. In case of contact with skin or eyes, wash immediately with water. Refer to Safety Data Sheet for more information.

Technical support:

Contact your sales representative for any questions or send an email to support@solisbiodyne.com

Online chat is available at www.solisbiodyne.com

DS-04-11-125 v2
Revised 18.10.2021

Permitted Use: This product is supplied for research use only (the **Permitted Use**). If the customer wishes to use the product for any purpose other than the Permitted Use, including (without limitation) resale or alteration, the customer should obtain the appropriate licence from Solis BioDyne. Some applications of this product may require a license/licenses from one or more third parties which are not provided by the purchase of this product. Users should obtain the licence if required. Covered by the patent EP2501716, made by the methods of US Patent No 9,321,999.

Trademark information: FIREPol® is an EU registered trademark of Solis BioDyne OÜ.

Warranty and Disclaimer: This product shall comply with its relevant specification and be fit for its stated purpose, but Solis BioDyne gives no other warranty and makes no representation as to description or quality. Any such warranty or representation is excluded, to the fullest extent permitted by law. In particular, but without limiting the foregoing, Solis BioDyne shall not be liable for the failure of the product to comply with its relevant specification where such failure arises as a result of: (i) customer negligence or because the customer failed to follow any of the applicable technical data or safety sheets, standard user materials, use guidelines or any other information provided by Solis BioDyne as to the storage, transportation, handling, use or maintenance of the products or other good practice regarding the same, or (ii) the customer altering the products in any way without the prior written consent from Solis BioDyne, or (iii) the products differing from the relevant specification as a result of changes made to ensure their compliance with applicable statutory or regulatory requirements.

Nothing shall limit or exclude Solis BioDyne's liability for death or personal injury caused by its negligence, fraud or fraudulent misrepresentation or any matter in respect of which it would be unlawful for Solis BioDyne to exclude or restrict liability. Without limiting the foregoing, Solis BioDyne shall under no circumstances whatever be liable to the customer, whether in contract, tort (including negligence), breach of statutory duty, or otherwise, for any loss of profit, or any indirect or consequential loss arising under or in connection with the products and Solis BioDyne's total liability to the customer in respect of all other losses arising under or in connection with the product, whether in contract, tort (including negligence), breach of statutory duty, or otherwise, shall in no circumstances exceed the price of the products supplied in respect of which the liability has arisen.

Solis BioDyne

Teaduspargi 9, 50411 Tartu, Estonia, tel: +372 740 9960, fax: +372 740 2079, e-mail: info@solisbiodyne.com, www.solisbiodyne.com