Stainless Steel Multi-Branch Manifold

Features

Quick-assembly and disassembly

Each component can be removed easily by hand for cleaning and autoclaving to prevent biofilms and eliminates sources of contamination.

Convertible funnel adaptor

Convertible funnel adaptor design allows user to fit the desired funnel (reusable or disposable) easily.

> Innovative vent valve design

An adjustable vent valve integrated with the pipe can eliminate water hammer phenomenon and help drain out residual waste water.

Ouick-Fit hose barb

Detachable hose barb can be connected to either side of the manifold quickly towards the vacuum source.

> Individual control valve

Each branch permits individual control.

Applications

- Filtration for microbiology test
- Chemical experiment
- General laboratory filtration

Ordering Information

180300-01

MultiVac 300-MS, 3 Places S.S. Manifold with No. 8 stopper funnel adaptor

180600-01

MultiVac 600-MS, 6 Places S.S. Manifold with No. 8 stopper funnel adaptor

200300-01 MF 3, 300ml Magnetic Filter Holder with lid kit

200500-01 MF 5, 500ml Magnetic Filter Holder with lid kit

167110-16

No.8 Silicone Stopper





Specification

Model	MultiVac 300-MS	MultiVac 600-MS
Number of branch	3	6
Filter diameter	Optional	Optional
Funnel capacity	Optional	Optional
Effective filtration area	Optional	Optional
Port thread	5/16 inch (8 mm)	5/16 inch (8 mm)
Dimension (LxWxH)	48 x 13 x 16 cm	85 x 13 x 16 cm
Part	Material	Material
Body	SUS316	SUS316
Control valve	SUS316	SUS316
Funnel support base	SUS316	SUS316
Handle/Knob	aluminum	aluminum
Connector	SUS316	SUS316