DATA SHEET WEEJET

REF : WL-J1-0X

FEATURES: Coverall with hood. Elasticated hood, waist, cuffs, and ankles. Thumb loop.
Double Self-adhesive storm flap and chinflap

FABRICS AND SEAMS: HDPE Film laminated and spunbonded polypropylene 88 ^{GSM}, taped seams

PHYSICAL PERFORMANCE			
Fabric Physical Properties	**Test Method**	**Results**	**Class**
Abrasion resistance	EN530	>2000 cycles	Class 6
Flex cracking	ISO 7854 B	>100 000	Class 6
Trapezoidal Tear	ISO 9073-4	40 N / 60 N	Class 3
Tensile strength	ISO 13934-1	60 N / 100 N	Class 2
Puncture resistance	EN863	10 N / 50 N	Class 2
Resistance to ignition	EN 13274-4	Pass	

FABRIC RESISTANCE TO PENETRATION BY LIQUIDS EN ISO 6530			
Fabric Chemical Properties		**Penetration**	**Repellency**
Sulphuric Acid 30%		Class 3	Class 3
Sodium Hydroxide 10%		Class 3	Class 3
O-Xylène		Class 3	Class 3
Bulan-1-ol		Class 3	Class 3

FABRIC AND TAPED SEAMS RESISTANCE TO PERMEATION BY LIQUIDS ENISO 6529			
Chemicals	**Synonyms**	Breakthrough time **(min)**	**Class**
Sulphuric Acid 96%	Oil of Vitriol	> 480 min	Class 6/6
Nitric acid (70%)		> 480 min	Class 6/6
Phosphoric acid (85%)		> 480 min	Class 6/6
Sodium Hydroxide 50%	Caustic Soda / Soda Lye	> 480 min	Class 6/6
Hydrochloric Acid 37%		> 480 min	Classe 6/6
Hydrochloric Acid 32%		> 480 min	Classe 6/6

FABRIC RESISTANCE TO PENETRATION OF INFECTIVE AGENTS EN14126	
Resistance to penetration by blood-borne pathogen ISO16604	Class 6/6
Resistance to penetration by contaminated liquids EN ISO22610	Class 6/6
Resistance to penetration by biologically contaminated aerosols EN ISO22611	Class 3/3
Resistance to penetration by contaminated solid particles ISO22612	Class 3/3

WHOLE SUIT TEST PERFORMANCE	
Liquid tight suits and Spray Tight Suits **Type 3B EN 14605**	Pass
High level spray test **Type 4B EN14605**	Pass
Dry particles **Type 5 B** Method as defined by **EN ISO 13982-1:2004 + A1:2010**	Pass
Light splashes **Type 6 B** Method as defined by **EN 13034 : 2005 +A1: 2009**	Pass
Barrier to infective agents **EN14126**	Pass
Protection factor according to **EN 1073-2:2002**	Class 1
Surface resistivity **EN 1149-5**	Pass
Seam Strength **ISO 13935-2**	Class 4

CHART SIZE			
Size	WeeSafe reference	Body Height	Chest
M	WL-J1-**02**	170-176 cm	92-100 cm
L	WL-J1-**03**	176-182 cm	100-108 cm
XL	WL-J1-**04**	182-188 cm	108-116 cm
XXL	WL-J1-**05**	188-194 cm	116-124 cm

PACKAGING				
	Units	Weight	Size	Volume
Carton	25	13 KG	52 X 32 X 41 CM	0,0682 ^{M3}
Pallet	400	208 KG	80 X 120 CM	1.0912 ^{M3}

GENCOD									
CARTON	**M**	3701012801933	**L**	3701012801797	**XL**	3701012801810	**XXL**	3701012801834	**XXXL**
POLYBAG		3701012801926		3701012801780		3701012801803		3701012801827	

CUSTOM CODE : 6210109800

DOMINIQUE DUTSCHER SAS

WeeSafe – IMMEUBLE "LE FUJY"- 1 RUE DU CENTRE 93160 NOISY-LE-GRAND - FRANCE – Tél : + 33 (0)1 43 09 98 04
Courriel : contact@weesafe.fr