Sicherheitsschrank Typ 30 - EN 14470-1 - Hoch 1 Tür - 5 Schubladen

ÜBEREINSTIMMUNG


EN 14470-1, FM 6050

ADVANTAGES

- 30-minute fire resistant and made in France
-
- Storage of flammables

SONDERN AUCH...

- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Adjustable leveling feet for enhance stability
- Geeignet für den Transport mit Hubwagen
- Tested and approved according to FM 6050
- Drawers with automatic closure in case of a fire



TECHNISCHE DATEN

Referenz	**3034T5**	Verriegelung der Türen	**selbstschließend**
Übereinstimmung	**EN 14470-1, FM 6050**	Versandabmessungen HxBxT (mm)	**2180 x 1200 x 800**
Baustoffe der Sicherheitschränke	**Melamine**	Belüftung	**zuluftöffnung und abluftöffnung auf dem dach**
Türfarbe	**hellgrau RAL 7035**	Durchmesser der Öffnungen (mm)	**100**
Anzahl der Türen	**2**	Anzahl der Abteile / Fächer	**1**
Art der Türen	**flügeltüren**	Codenummer	**94036000**
Scharniere	**rechts**		

COMPLEMENTARY ACCESSORIES - VENTILATION AND FILTRATION BOXES

- Filteraufsätze mit filter für organische Dämpfe (Réf : CDF-A)
- Lüftungskasten (Réf : CDV-A)
- Filteraufsätze (ohne Filter) - NF X 15-211 (Réf : H50C)
- Anschlussse für Filteraufsätze (Réf : KRC)

Referenz	Äußere Abmessungen HxBxT (mm)	Innere Abmessungen HxBxT (mm)	Lagerkapazität (L)	Auffangwanne	Regale	Tragfähigkeit	Gewicht (Kg)
3034T5	1980 x 605 x 550	1581 x 491 x 419	130		0	30	147.00

DOMINIQUE DUTSCHER SAS

TRIONYX
1er FABRICANT FRANÇAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr