Filterabzug mit 2 Hand Passage - NF X 15-211

ÜBEREINSTIMMUNG

NF X 15-211

ADVANTAGES

- CE certified
- NF X 15-211 compliant
- Storage of flammables, corrosives and toxics

SONDERN AUCH...

- NF X 15-211 compliant
- Delivered ready to use
- Ergonomic hand traps or trapezoidal opening
- Front control window to see immediately the filter
- Easy replacement of the active coal filter
- Low acoustic level
- Glass side walls
- Lighting control allowing to survey the proper working of the fan
- Adjustable leveling feet for enhance stability
- Containment sump integrated



TECHNISCHE DATEN

Referenz	**H70**	Zeitzähler	**Ja**
Übereinstimmung	**NF X 15-211**	Probenahme	**Ja**
Einströmgeschwindigkeit (m/s)	**0,5**	Transparente Rückwand	**Nein**
Elektrische Spannung (volts)	**220-240**	Arbeitsplan aus Melamin	**Ja**
Durchflussstrom (m3/h)	**170**	Anschlusswert (W)	**10**
Anemometer	**Ja**	Geräuschpegel des Ventilators	**57.00**
Leitfaden der ausgewählten Produkte	**Ja**	Codenummer	**84146000**

PRODUITS COMPLÉMENTAIRES

- Activkohlefilter für Ammoniak Dämpfe - for old fume hoods type 200, 201, 210 and 211 (Réf : AMM200)
- Aktivkohlefilter für organische und korrosive Dämpfe - for filtration box H50C (or old cabinets range 12.X before 2002) (Réf : CORG51)
- Aktivkohlefilter für Formaldehyd Dämpfe - for filtration box H50C (or old cabinets range 12.X before 2002) (Réf : FOR50)
- Aktivkohlefilter für organische Dämpfe - for filtration box H50C (or old cabinets range 12.X before 2002) (Réf : ORG50)

Referenz	Äußere Abmessungen HxBxT (mm)	Innere Abmessungen HxBxT (mm)	Gewicht (Kg)
H70	605 x 505 x 485	410 x 455 x 445	1.00

DOMINIQUE DUTSCHER SAS

TRIONYX
1er FABRICANT FRANÇAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr