eppendorf



## The New Legend

Eppendorf Reference® 2 Pipette



# »The new Reference class for modern liquid handling tools.«

The name »Reference« stands for extraordinary precision and accuracy, a long service life, and an ergonomic design. The new Reference 2 boasts these proven Premium characteristics and this operating philosophy with its innovative state of the art technology; making it a reliable partner for you and your demanding work.







### Unique upper handle

- > Round shape makes it possible to work in every position
- > Smooth surface for easy cleaning
- > External edges made from stainless steel for outstanding robustness at potential impact sites
- > 4-digit display for exact volume setting and secure volume lock

#### Multi-channel version

- > Channel indicator guarantees continuously identical pipette alignment during the work process
- > Spring-loaded tip cones for reproducible tip fit and reduced effort (to be switched on/off optionally)
- > Simple maintenance with the ability to remove single cones

### User friendly adjustment

- > The Reference 2 provides user adjustment for liquids other than aqueous solutions leaving factory settings untouched
- > Suggestions for settings are provided
- > Reset back to manufacturer setting just as quick and easy

## The Eppendorf Reference® 2 at a Glance



> Fully autoclavable

\* The Reference 2 pipette is designed and constructed for low-contamination transfer of liquids, in particular for samples from the human body and for reagents within the scope of an in-vitro diagnostic application in order to allow the in-vitro diagnostic medical device to be used as

intended. This pipette is an in vitro diagnostic device according to Directive 98/79/EC of the European Parliament and the Council dated October 27, 1998. It is intended exclusively for indoor use and for operation by qualified staff.



## Sturdy Upper Handle

> Guarantees long service life and increased robustness

## Optimized surface

- > Few rough edges
- > Smooth surface for comfortable working and simple cleaning

## Additional advantages:

- > High precision and accuracy provides reliable pipetting results
- > User friendly secondary adjustment
- > Customizable labeling area

## Single-button operation

- > Ergonomic handling with reduced operating effort.
- > Simple and quick tip ejection with active aerosol reduction
- > Reduce repetitive strain injuries by not having to move your thumb sideways
- > Haptic feedback before tip ejection

Description	Volume	Systematic error		Random error		Order no. (International)	
		± %	± μL/mL	± %	± μL/mL		/
Eppendorf Reference® 2, single-channel vari	able*						
0.1–2.5 μL ■ dark gray	0.1 μL	±48.0	±0.048	±12.0	± 0.012	4920 000.016	
	0.25 μL	±12.0	±0.03	±6.0	±0.015		
	1.25 μL	±2.5	±0.031	±1.5	±0.019		
	2.5 μL	±1.4	±0.035	±0.7	±0.018		_
0.5–10 μL ■ medium gray	0.5 μL	±8.0	±0.040	±5.0	±0.025	4920 000.024	
	1 μL	±2.5	±0.025	±1.8	±0.018		
	5 μL	±1.5	±0.075	±0.8	±0.04		
	10 μL	±1.0	±0.10	±0.4	±0.04		_
2–20 μL	2 μL	±5.0	±0.10	±1.5	±0.03	4920 000.032	
■ light gray	10 μL	±1.2	±0.12	±0.6	±0.06		
	20 μL	±1.0	±0.20	±0.3	±0.06		_
2–20 µL ■ yellow	2 μL	±5.0	±0.10	±1.5	±0.03	4920 000.040	
	10 μL	±1.2	±0.12	±0.6	±0.06		
	20 μL	±1.0	±0.2	±0.3	±0.06		_
10−100 μL ■ yellow	10 μL	±3.0	±0.3	±0.7	±0.07	4920 000.059	-
	50 μL	±1.0	±0.5	±0.3	±0.15		
	100 μL	±0.8	±0.8	±0.20	±0.20		
20–200 μL	20 μL	±2.5	±0.5	±0.7	±0.14	4920 000.067	-
yellow yellow	100 μL	±1.0	±1.0	±0.3	±0.3		
	200 μL	±0.6	±1.2	±0.2	±0.4		
30–300 μL ■ orange	30 μL	±2.5	±0.75	±0.7	±0.21	4920 000.075	-
	150 μL	±1.0	±1.5	±0.3	±0.45		
	300 μL	±0.6	±1.8	±0.2	±0.6		
100–1000 μL ■ blue	100 μL	±3.0	±3.0	±0.6	±0.6	4920 000.083	-
	500 μL	±1.0	±5.0	±0.2	±1.0		
	1000 μL	±0.6	±6.0	±0.2	±2.0		
0.25-2.5 mL	0.25 mL	±4.8	±0.012	±1.2	±0.003	4920 000.091	-
red	1.25 mL	±0.8	±0.010	±0.2	±0.0025		
	2.5 mL	±0.6	±0.015	±0.2	±0.005		
0.5-5 mL	0.5 mL	±2.4	±0.012	±0.6	±0.003	4920 000.105	-
purple	2.5 mL	±1.2	±0.030	±0.25	±0.006		
	5.0 mL	±0.6	±0.030	±0.15	±0.0075		
1–10 mL turquoise	1.0 mL	±3.0	±0.030	±0.6	±0.006	4920 000.113	-
	5.0 mL	±0.8	±0.040	±0.2	±0.010		
	10.0 mL	±0.6	±0.060	±0.15	±0.015		
Eppendorf Reference® 2, 8- and 12-channel va						8-channel	12-channe
0.5–10 μL	0.5 μL	±12.0	±0.06	±8.0	±0.04	4922 000.013	4922 000.02
I medium gray	1 μL	±8.0	±0.08	±5.0	±0.05	., 000.013	., 000.02
	5 μL	±4.0	±0.2	±2.0	±0.03		
	<u>3 με</u> 10 μL	±4.0 ±2.0	±0.2	±1.0	±0.1		
0-100 ul	10 μL	±3.0	±0.2	±2.0	±0.1	4922 000.030	4922 000.04
10−100 μL yellow	50 μL	±1.0	±0.5	±0.8	±0.2 ±0.4	T/22 000.030	7722 000.02
	100 μL	$\pm 0.8$	±0.5 ±0.8	±0.8 ±0.3	±0.4 ±0.3		
80–300 ul	30 μL	±3.0	±0.8	±0.3 ±1.0	±0.3	4922 000.056	4922 000.00
30−300 µL orange  * All Eppendorf Reference 2 single-channel adjustable-volume pipettes come	30 μL 150 μL	±1.0	±1.5	±0.5	±0.3 ±0.75	T722 000.030	4722 000.00
		_			±0.75		
	300 μL	±0.6	±1.8	±0.3	<b>±</b> ∪.7		

**Ordering information** 

Description	Color code	Systematic error		Random error		Order no.
		± %	$\pm \mu L/mL$	± %	$\pm \mu L/mL$	(International)
Eppendorf Reference® 2, single-channel fixed		•	_			
1 μL	dark gray	±2.5	±0.025	±1.8	±0.018	4921 000.010
2 μL	dark gray	±2.0	±0.04	±1.2	±0.024	4921 000.028
5 μL	medium gray	±1.2	±0.06	±0.6	±0.03	4921 000.036
10 μL	medium gray	±1.0	±0.1	±0.5	±0.05	4921 000.044
10 μL	yellow	±1.2	±0.12	±0.6	±0.06	4921 000.052
20 μL	☐ light gray	±0.8	±0.16	±0.3	±0.06	4921 000.060
20 μL	yellow	±1.0	±0.2	±0.3	±0.06	4921 000.079
25 μL	yellow	±1.0	±0.25	±0.3	±0.075	4921 000.087
50 μL	yellow	±0.7	±0.35	±0.3	±0.15	4921 000.095
100 μL	yellow	±0.6	±0.6	±0.2	±0.2	4921 000.109
200 μL	yellow	±0.6	±1.2	±0.2	±0.4	4921 000.117
200 μL	blue	±0.6	±1.2	±0.2	±0.4	4921 000.125
250 μL	blue	±0.6	±1.5	±0.2	±0.5	4921 000.133
500 μL	blue	±0.6	±3.0	±0.2	±1.0	4921 000.141
1000 μL	blue	±0.6	±6.0	±0.2	±2.0	4921 000.150
2 mL	red	±0.6	±0.012	±0.2	±0.004	4921 000.168
2.5 mL	red	±0.6	±0.015	±0.2	±0.005	4921 000.176
Accessories						
Pipette carousel Eppendorf Reference 2						4923 000.009

Technical specifications subject to change. Errors and omissions excepted.



Your local distributor: www.eppendorf.com/contact Eppendorf AG  $\cdot$  22331 Hamburg  $\cdot$  Germany eppendorf@eppendorf.com  $\cdot$  www.eppendorf.com

www.eppendorf.com/reference2

Eppendorf®, the Eppendorf Logo, PhysioCare Concept®, Eppendorf Reference® and epT.I.P.S.® are registered trademarks of Eppendorf AG, Germany. U.S. Design Patents are listed on www.eppendorf.com/ip. All rights reserved, including graphics and pictures. Carbon neutrally printed in Germany. Copyright © 2016 by Eppendorf AG. Order No.: A492012 021/IVD/GBI/0T/0916/NW