

eppendorf

General Lab Product



The Next Benchmark

The new refrigerated Centrifuge 5910 R



Compact footprint

Outstanding rotor versatility

Menu-operated display incl. 5 program keys for easy access to routine programs

Quiet operation

The Next Benchmark in Centrifugation Technology

The new refrigerated Centrifuge 5910 R combines extraordinary versatility with high capacity in a compact and ergonomic product design. It shares the modern user interface and advanced technology of its bigger brother, the Centrifuge 5920 R, which lab users have come to love.

Outstanding versatility for all your applications

- > Broad rotor and adapter selection to spin all commonly used tubes, bottles, and plates
- > High centrifugation speed up to $22,132 \times g$ (14,000 rpm) for applications in tubes from 0.2 to 750 mL and plates
- > Aerosol-tight rotors (e.g. for potentially hazardous materials) for both tubes and plates

Ergonomic operation

- > Low sound level to benefit your work environment
- > Low access height for easy loading/unloading
- > Centrifuge lid with soft-touch lid closure
- > Compact footprint saves valuable bench space
- > Eppendorf QuickLock® caps and lids allow fast and ergonomic lid-locking

Advanced temperature management for maximum sample protection and energy efficiency

- > Temperature range from -11 °C to 40 °C
- > FastTemp function for quick pre-cooling
- > FastTemp pro® function allows for automatic precooling based on pre-programmable time and date
- > Standby cooling function holds temperature when centrifuge is not in use
- > ECO shut-off engages after 8 hours (adjustable) of non-use to reduce energy consumption and extend compressor life

Main swing-bucket rotors

Rotor S-4xUniversal

- > High capacity swing-bucket rotor with max. speed $4,347 \times g$ (4,500 rpm)
- > Universal rotor buckets for spinning tubes and plates
- > Universal adapters hold 15 or 50 mL conical tubes and plates.

Benefit: No rotor bucket or adapter change needed.



Rotor S-4x750

- > High-capacity swing-bucket rotor with max. speed $4,800 \times g$ (4,700 rpm)
- > Mixed loading with 2 plate buckets and 2 round tube buckets allows for increased versatility

Ordering Information

Technical specifications

Description	
Max. rcf	
> Fixed-angle rotor	22,132 × g
> Swing-bucket rotor	5,263 × g (Rotor S-4x400)
Speed	100 – 14000 rpm (in 10 rpm increments)
Max. capacity	4 × 750 mL / 4 × 2 DWP
Accel. / Braking ramps	10 / 10
Programs	99 (5 program keys)
Timer	10 s – 99 h 59 min, infinite
Temperature control range	-11 °C to 40 °C
Noise level	
> Rotor S-4xUniversal	< 53 dB(A)
> Rotor FA-6x50	< 58 dB(A)
Power supply	230 V/50–60 Hz
Max. power consumption	1,650 W
Dimensions (W × D × H, incl. front panel)	72 × 66 × 37 cm
Footprint (dimensions w/o front panel, W × D)	72 × 62 cm
Height with open lid	85 cm
Weight without rotor	109 kg

Technical specifications subject to change. Errors and omissions excepted.

Ordering information

Description	Max. capacity of conical tubes per rotor	Order no.
Centrifuge 5910 R, 230 V/50 – 60 Hz		5942 000.010
Centrifuge 5910 R, with Rotor S-4xUniversal, incl. universal buckets and adapters for 5 mL/15 mL/50 mL conical tubes and plates	64 × 15 mL/36 × 50 mL	5942 000.315
Centrifuge 5910 R, with Rotor S-4xUniversal, incl. universal buckets and adapters for 5 mL/15 mL/50 mL conical tubes, 175 mL – 250 mL bottles and plates	64 × 15 mL/28 × 50 mL	5942 000.215
Centrifuge 5910 R, with Rotor S-4x750, incl. round buckets and adapters for 15 mL/50 mL conical tubes	56 × 15 mL/28 × 50 mL	5942 000.515
Centrifuge 5910 R, with Rotor S-4x500, incl. rectangular buckets and adapters for 15 mL/50 mL conical tubes	48 × 15 mL /20 × 15 mL	5942 000.615
Centrifuge 5910 R, with Rotor S-4x400, incl. round buckets and adapters for 15 mL/50 mL conical tubes	28 × 15 mL /16 × 50 mL	5942 000.710

For further information about swing-bucket and fixed-angle rotors, please contact your local Eppendorf organization.

Your local distributor: www.eppendorf.com/contact
 Eppendorf AG · Barkhausenweg 1 · 22339 Hamburg · Germany
eppendorf@eppendorf.com · www.eppendorf.com

www.eppendorf.com/next-benchmark