

Sartolab[®] RF 50

Vacuum filtration unit
for volumes up to 50 mL

User Benefits

- Highest flow rates with an asymmetric membrane and a large filtration surface
- No loss of protein with a low protein affinity membrane
- Low dead volume due to an optimized membrane support
- Minimized risk of contamination with a complete ready-to-use unit (no additional transfer of liquid necessary for storage)
- May be used as a standalone system or with the Sartolab[®] MultiStation, which allows parallel filtration of up to 6 samples

Product Information

Sartolab[®] RF 50 vacuum filtration units are single-use units for the filtration of sample volumes up to 50 mL. They are available with either a 0.22 or 0.45 µm polyethersulfone membrane.

Both membranes provide fast flow rates and ensure low protein binding and extractables. Both versions are individually-packed, sterile, and ready to use. The 0.22 µm version is ideal for sterile filtration of cell cultures, buffers, and aqueous solutions, while the 0.45 µm version is ideal for clarification.




The Sartolab® RF 50 vacuum filtration unit comprises the following:

- a funnel, with dust cover
- a 50 mL conical tube, with graduation and writing field
- a tubing connector for vacuum connection
- a screw cap for storage of your filtrate (individually wrapped to maintain sterility)

The design of the yellow adapter connecting the funnel to the conical tube ensures a vacuum-tight seal and enables the filtration unit to be used on the Sartolab® MultiStation for filtration of up to 6 samples in parallel with one vacuum source. However, Sartolab® RF 50 can also be used alone by directly connecting the unit's tubing connector to your vacuum source.

Sartolab® RF 50 is the fastest 50 mL vacuum filtration unit compared to 4 of the leading competitor's units

Comparison of filtration times for 50 mL cell media + 10% FBS in five 0.22 µm 50 mL vacuum filtration units



Materials

Funnel with dust cover	Styrene-acrylonitrile (SAN)
Membrane filter	0.22 µm polyethersulfone (order no. 180E01) 0.45 µm polyethersulfone (order no. 180F01)
Funnel adapter	Polyethylene
Tubing connector for vacuum connection	Polyethylene
Conical tube	Polypropylene
Conical tube cap	Polyethylene

Specifications

Membrane diameter	58.5 mm
Effective filtration area	21 cm ²
Hold-up volume	1.2 mL
Filtration capacity	50 mL
Size of the 50 mL conical tube	Height: 115.5 mm External/internal diameter: 29.5 mm/27.48 mm
Autoclavable	No
Sterilization method	E-Beam (beta) irradiation
Storage temperature of the conical tube	-80°C to max. 100°C
Packaging	Single-packaged, sterile
Operating pressure	350 to -700 mbar

Ordering Information


Order Number	Description	Quantity
180E01----2	Sartolab® RF 50, 0.22 µm, PES	24 units
180F01----2	Sartolab® RF 50, 0.45 µm, PES	24 units

Germany

Sartorius Lab Instruments GmbH & Co. KG
Otto-Brenner-Strasse 20
37079 Goettingen
Phone +49 551 308 0

USA

Sartorius Corporation
565 Johnson Avenue
Bohemia, NY 11716
Phone +1 631 254 4249
Toll-free +1 800 635 2906

 For further information, visit
www.sartorius.com